

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 7 Page(s) 2892)

Set post, 3 ft. long, & 3" sq., 24" in the ground for the ¼ sec. cor. marked ¼ S on N face, from which:
A laurel, 6" dia., bears S.70°E., 19 lks., mkd: ¼ S BT.
A laurel, 7" dia., bears N.19°W., 10 lks., mkd: ¼ S BT.

BLM dependent resurvey Levi E Tallett, Cadastral Engineer (1951) and C. Albert White, Cadastral Surveyor (1963), under Group # 294, surveyed May 1951 - Aug 1963 - (DCSO records Vol. 32 Page(s) 13291)

Point for the ¼ sec. cor. of secs. 25 & 36, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 36 long, 1" dia., 28" in the ground with brass cap marked:
$$\frac{1}{4} \begin{array}{r} S 25 \\ S 36 \\ 1951 \end{array}$$

A fir, 40" dia., bears N.31½°W., 60 lks., mkd: ¼ S25 BT.
A fir, 24" dia., bears S.31½°E., 32 lks., mkd: ¼ S36 BT.

Dan Saily & Ken Hoffine - For: Lone Rock TT Landco, LLC - 7/2021 - M179-65

Found - BLM 1951 brass cap marked ¼ S25/536.
40" record D.Fir is now heavily decayed 6 ft-tall stub remains which bear N.31°W., 38.3 ft (record 39.6 ft) no marks but old "BT" paint
24" D.Fir heavily burned solid stump bears S.31°E., 21.3 ft with no marks remaining and a burned BLM tag which we nail back onto stump along with a new tag.
16" Maple with a burned-out face four ft high on tree bears N.50°W., 21.05 ft, we tag tree monument is 1 ft tall and bent to lean to the NW on an extremely steep boulder strewn rocky north slope which was heavily burned in the Archie Fire
Note - All conifer trees within 150 ft are heavily burned or down. We put 5 ft U-Post 0.75 ft east of where the pipe enters the ground.
Rock bluff ridge point bears SW 140 ft along the section line.