

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 24 & 25

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 7 Page(s) 2894)

Set a basalt stone 16x6x6" 11" in the ground for ¼ sec. cor. mkd: ¼ S on N face, from which
A laurel, 14" dia., bears N.78°30'E., 10 lks., mkd: ¼ S BT
A laurel, 14" dia., bears S.78°W., 13 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - 6/21/1967 - C.S. File 52/42-53

REPORTED AS NOT FOUND
From Post card sent to Office dated 6/15/1967:
2 orig. Laurel BTs & stone with 2 notches. Could not find "¼S" on stone. Noted: 1 bearing does not check.
Remarks: Orig. E-W line blazes go directly to this corner. Fd. 2 notches on stone but did not find "¼S" on it. BTs are in perfect position with each other and the stone.

6/21/1967 VRT report:
We find no scribe marks on either tree. Nor do we find mkd. stone.
Insufficient evidence to renew.

Dennis O. Bryant - For: Winchester Plywood - C.S. File 55/55-2

Locate a basalt stone with 2 chisel marks from which:
14" now 40" Madrone (Laurel) bears N.78°30'E., 6.6 ft.
14" now 22" Madrone (Laurel) bears S.78°E., 8.6 ft.
I set a 1" dia. Iron bolt from which:
7" DBH D.F. "¼ S25 BT" which is S.45°E., 6.3 ft.
11" DBH D.F. "¼ S24 BT" which is N.45°E., 25.8 ft.