

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 24

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 7 Page(s) 2896)

Set a basalt stone 18x12x12" 12" in the ground for ¼ sec. cor. marked ¼ on N face, from which
A hemlock, 18" dia., bears S.63°W., 25 lks., mkd: ¼ S BT.
A fir, 30" dia., bears N.55°30'W., 33 lks., mkd: ¼ S BT.

Dennis O. Bryant - For: Winchester Plywood - C.S. File 55/55-3

Found - A pile of stone & 2 Orig. BTs as follows:
18" now 30" Hemlock bears S.63°W., 16.5 ft.
30" D.Fir now a snag, bears N.55°30'W., 21.78 ft.
Set - 1" iron pipe with brass cap in mound of stone.
New BT - 8" Hemlock bears N.25°E., 8.5 ft., mkd: "¼S S13 BT"

Fd. Ok by VRT, DCSO 7/12/1968 C.S. File 54/27-222

David Edwards - Brant Miller & Eric Sprinkle, Crew - 12/2020 - C.S. File 65/106-67

Found - The lower 6" of the iron pipe set on C.S. 55/55-3. Brass cap missing.
A 40" dia. Hemlock bears S.65°W., 15.9' Rec. (S.63°W., 16.5')
A 30" dia. rotted Fir snag bears N.57°W., 23.0' Rec. (N.55°30'W., 21.78')
A 20" dia. Hemlock stump bears N.23°E., 8.3' Rec. (N.25°E., 8.5')

Set A 5/8" x 30" steel rebar at the found pipe position with 2½" dia. aluminum cap mkd. "Roseburg Resources Co." and "¼ S13 and S24" and 2339" and "2020".
An 11" dia. Fir bears N.76°E., 8.5' scribed "¼ S13 BT"
A 12" dia. Fir bears N.9°W., 20.0' scribed "¼ S13 BT"

Note - No suitable trees in Section 24.
Compass decl. 15°E.