

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 640600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 & 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619 dated June 5, 1893 - (DCSO records Vol. 7 Page(s) 2900)

-----  
Set post, 3 ft. long, & 3" sq., 24" in the ground for the ¼ sec. cor. marked ¼ S on N face, from which:  
A hemlock, 20" dia., bears N.20°W., 8 lks., mkd: ¼ S BT.  
A fir, 20" dia., bears S.41°E., 41 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John Powell - Willie Penley - Aug. 1970 - C.S. File 54/27-227

-----  
Found - 20" now 32" Hemlock, N.20°W., 5.3 ft., shows good scar.  
20" now 30" D.Fir, S.41°E., 27.1 ft., shows good scar.  
Very good E-W blazed line. Old forest appraisal tag, & cruisers marks.  
Set - Brass cap at cor. mkd: County Surveyors T24S R2W  
Office S 1  
1970 S 12

BTs Ok & tagged.  
Note - Paced call 9 chs. E. to creek hits good. Due to call faces on trees, bearing & dist. to trees & line, I did not open BTs.