

PRIMARY CORNER DESCRIPTION SE. Corner for Sec. 36

| Alias | Description |
|-------|-------------|
| _____ | _____ |
| _____ | _____ |
| _____ | _____ |
| _____ | _____ |

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 8 Page(s) 3481)

Set post 4½ ft. long, 4" sq., 24" in ground for cor. to Tps. 24 and 25 S., Rgs. 1 and 2 W. marked T24S S31 on NE.; R1W S6 on SE.; T25S S1 on SW.; and R2W S36 on NW., faces with 6 notches on each edge, from which

- A Fir 14" dia., bears N.20°E., 16 lks. dist. mkd. T24S R1W S31 BT.
- A Fir 12" dia., bears S.60½°E., 22 lks. dist. mkd. T25S R1W S31 BT.
- A Fir 12" dia., bears S.63°W., 32 lks. dist. mkd. T25S R2W S1 BT.
- A Fir 14" dia., bears N.25°W., 15 lks. dist. mkd. T24S R2W S36 BT.

Fd. and used McQuinn's corner in GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 7 Page(s) 2889-90)

GLO survey by Carl S. Nicklin, Deputy Surveyor, under contract #664 dated May 23, 1896 (DCSO records Vol. 7 Page(s) 2776¼)

This corner, which is a post 2" sq., 2 ft. above ground, marked and witnessed as described by the Surveyor General. I re-establish this cor. as follows:

Set a Fir post 4 ft. long, 4' sq., 24" in the ground for cor. of T 24 and 25 S., R. 2 W., on W. bdy. of T24S R1W, marked: T24S R2W S36 on NW.; T25S R2W S1 on SW. faces; with 6 notches on N., W., and S. edges, from which

- A Fir 14" dia., bears N.16°W., 16 lks. dist. mkd. T24S R2W S36 BT.
- A Fir 14" dia., bears S.58°W., 33 lks. dist. mkd. T25S R2W S1 BT.

This cor. is on a steep hillside sloping N. about 300 ft. below the closing cor. of Ts. 24 and 25 S., R 2 W.

BLM resurvey by Levi E. Tallett and C. Albert White, Cadastral Surveyors, under Group #294, Surveyed May 1951/Aug. 1963 - (DCSO records Vol. 32 Page(s) 13276)

"The intermediate corners along this line which were established by McQuinn formerly referred only to T. 24 S., R. 2 W. The purported retracement of the south boundary of sec. 31 and the reported establishment of closing corners on the (Cont. Next Page)

PRIMARY CORNER DESCRIPTION SE. Corner for Sec. 36

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

boundary by Hezekiah Johnson in 1900 **having proved to be fictitious**, the McQuinn corners except for the south ¼ sec. cor. of sec.31 and the south ¼ sec. cor. of sec. 36, are changed in 1963 to corners of maximum control in order to provide a basis for Consent Decree "Civil No. 60-135, Oregon."

The cor. of Tps. 24 and 25 S., R. 2 W., on the W. bdy. of Sec. 31, T24-1, determined at record distance from the original bearing trees:

- A Fir 30" dia., bears N.27°E., 16 lks. dist., with blaze healed. (Rec. brg. N.20°E.)
- A rotted stump bears S.56°E., 22 lks. dist. (Rec. brg. S.60½°E.)
- A Fir 18" dia., bears S.57½°W., 32 lks. dist., with partial scribe marks visible on blaze under 68 years of overgrowth. (Rec. brg. S.63°W.)

At the corner point

Set an iron post 36" long, 3" dia., 8" in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap marked:

| | |
|-------------|--------|
| T 24 S | |
| R 2 W | T 24 S |
| <u>S 36</u> | R 1 W |
| S 1 | S 31 |
| T 25 S | |
| 1951 | |

from which bearing trees mkd. in 1851:

- A Fir 18" dia., bears N.35½°W., 28 lks. dist. mkd. T24S R2W S36 BT.
- A Fir 20" dia., bears S.44½°W., 46 lks. dist. mkd. T25S R2W S1 BT.