

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 700168

PRIMARY CORNER DESCRIPTION C C for Secs. 30 & 31 only, T24-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 7 Page(s) 2843)

At point of intersection (11.58 chs. S.9°19'W. of cor. of secs. 36 and 25, T24-2) I set a Cedar post 4 ft. long, 4" sq., 24" in the ground for closing cor. of secs. 30 and 31 marked C C T24S R1W on E.; S30 on N.; and S31 on S. faces, with 5 grooves on N. and 1 groove on S. faces, from which
A Chinquapin 10" dia., bears N.67°E., 47 lks. dist. mkd. T24S R1W S30 BT.
A Hemlock 6" dia., bears S.43°E., 21 lks. dist. mkd. T24S R1W S31 BT.
This cor. is on a steep hillside, sloping N. about 90 ft. above creek.

BLM resurvey by Levi E. Tallett and C. Albert White, Cadastral Surveyors, under Group #294, Surveyed May 1951/Aug. 1963 - (DCSO records Vol. 32 Page(s) 13286)

The closing cor. is determined at record bearing and distance from the original SE. bearing tree:
A Hemlock 14" dia., bears S.43°E., 21 lks. dist., with scribe marks S3 visible on partially healed blaze.

Dan Saily & Ken Hoffine - For: Lone Rock TT Landco, LLC - 7/2021 - M179-65

Set - 5/8"X40" iron rod with 2½" aluminum cap mkd LONE ROCK TIMBER T24S R2W S36/ T24S R1W S30 S31 2021 PLS2291
9" D.Fir bears S.81½°W., 7.4 ft we scribe S36 BT and tag tree
18" D.Fir bears N.51¾°W., 21.80 ft we scribe X S36 BT and tag tree
19" Hemlock bears N.73¾°E., 22.55 ft we scribe T24S R1W S31 BT and tag tree
12" Hemlock bears N.47½°E., 23.52 ft we scribe T24S R1W S30 BT and tag tree.
Monument is 0.3 ft above ground and lies on a very steep north slope in a very old north-south cat fireline road 160 ft south of gravel road