

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36 only (East)

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GL0 survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 7 Page(s) 2873 and (duplicate pg.2761)

-----  
Set Cedar post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 31, 36, 25 and 30 marked T24S S30 on NE.; R1W S31 on SE.; R2W S36 on SW.; and S25 on NW. faces, with 1 notch on S. and 5 notches on N. edges, from which  
A Cedar 24" dia., bears N.40°E., 52 lks. dist. mkd. T24S R1W S30 BT.  
A Cedar 42" dia., bears S.75°E., 15 lks. dist. mkd. T24S R1W S31 BT.  
A Hemlock 12" dia., bears S.25°W., 15 lks. dist. mkd. T24S R2W S36 BT.  
A Hemlock 14" dia., bears N.20°W., 33 lks. dist. mkd. T24S R2W S25 BT.

GL0 survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 7 Page(s) 2939)

-----  
The Sec. cor., which is a Cedar post 2 ft. above ground mkd. as, but not witnessed as, described by the surveyor general. This cor. not being correct in position, I re-establish as follows:  
Set a Cedar post 4 ft. long, 4" sq., 24" in the ground for cor. of secs. 25 and 36, mkd. T24S S36 on SW. and R2W S25 on NW. faces, with 1 notch on S. and 5 notches on N. edges, from which  
A Hemlock 12" dia., bears S.27°W., 15 lks. dist. mkd. T24S R2W S36 BT.  
A Hemlock 12" dia., bears N.16°W., 35 lks. dist. mkd. T24S R2W S25 BT.

BLM resurvey by Levi E. Tallett and C. Albert White, Cadastral Surveyors, under Group #294, Surveyed May 1951/Aug. 1963 - (DCSO records Vol. 32 Page(s) 13286)

-----  
The cor. of secs. 25 and 36, determined from the NE. and SE. bearing trees:  
A Cedar 44" dia., bears N.40°E., 52 lks. dist., with scribe marks S20 T24 R BT visible.  
A fallen Cedar 46" dia., bears S.25°E., 15 lks. dist., blaze rotted. (Rec. brg. S.75°E.)  
At the corner point  
Set an iron post, 36" long, 2" dia., 28" in the ground, with brass cap mkd:  
(Cont. Next Page)

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36 only (East)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

T 24 S		T 24 S
S 25		R 1 W
S 36		S 30
R 2 W		
1951		

from which

A Cedar 10" dia., bears N.78°W., 97 lks. dist. mkd. T24S R2W S25 BT.

A Cedar 36" dia., bears S.32°W., 122 lks. dist. mkd. T24S R2W S36 BT.

BLM Resurvey by Lynn M. Roseberry, Cadastral Surveyor - Under Group #634 Surveyed, May 1967 - (DCSO records Vol. 34 Page(s) 14169-70)

-----  
The Sec. cor., determined at record bearing and distance from the remaining orig. bearing tree mkd. by McQuinn:

A Cedar 44" dia., bears N.40°E., 52 lks. dist., with scribe marks S20 T24 BT visible on partially healed blaze.

and the remaining bearing tree mkd. by Tallett:

A sawed Cedar stump 40" dia., bears S.32°W., 122 lks. dist., with scribe marks T24S R2W S36 BT visible on partially healed blaze.

At the corner point

Set an iron post 28" long, 2½" dia., 24" in the ground, with brass cap mkd.

T 24 S		T 24 S
S 25		R 1 W
S 36		S 30
R 2 W		
1967		

from which a new bearing tree

A Cedar 65" dia., bears N.50½°W., 135 lks. dist. mkd. T24S R2W S25 BT.

Corner is located at the NE. cor. of a logged area, and in the W. edge of a creek, 6 lks. wide, filled with logging debris, course N.25°W.

Dan Saily & Ken Hoffine - For: Lone Rock TT Landco, LLC - 7/2021 - M179-65

-----  
Set - 5/8"x40" iron rod with 2½" aluminum cap marked:  
LONE ROCK TIMBER T24S R2W S25/S36 T24S R1W S30  
2021 PLS2291

34" WR Cedar stump 6 ft tall bears record S.32°W., 80.52 FT 1967 BLM tag scribe visible on old chopped face. I first located this stump and signed tag MARCH 1987. Continued next page

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36 only (East)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Down fallen across draw remains of 65" WR Cedar where a stump hole on a steep side of draw bears approx. at record N.50°W., 89.1 ft no marks found  
40" WR Cedar stump 4 ft tall bears S.20°W., 17.3 ft we scribe XBT and tag the stump.  
9" D.Fir bears S.81½°W., 7.4 ft we scribe S36 BT and tag tree  
15" D.Fir bears N.51½°W., 43.2 ft we scribe S25 BT and tag tree  
45" WR Cedar stump 5 ft tall on uphill side of very steep slope bears N.56¼°E., 50.5 ft we scribe BT and tag the stump.  
9" WR Cedar bears S.63°E., 45.5 ft we scribe S36 BT and tag tree  
Monument is 0.1 ft above ground on the bottom west edge of very steep draw. The draws appears to have been subject to large debris flows in the past. The corner lies 3.5 ft SW of centerline of secondary creek and 23 ft SW of centerline of main creek which flows downhill northwesterly on the east edge of draw bottom.