

PRIMARY CORNER DESCRIPTION C C for Secs. 19 & 30, T24-1

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 7 Page(s) 2847)

At a point of intersection (9.75 chs. S.6°25'W. of cor. of secs. 24 and 25, T24-2), Set a basalt stone 12x10x8 ins., 8" in the ground, for closing cor. of secs. 19 and 30, mkd. C C on E. face, with 4 grooves on N. and 2 grooves on S. faces, from which

A Fir 12" dia., bears N.29°E., 12 lks. dist. mkd. T24S R1W S19 BT.

A Fir 20" dia., bears S.11°E., 45 lks. dist. mkd. T24S R1W S30 BT.

Cor. is on a steep hillside, sloping E. about 50 ft. above Rock Creek.

Survey by Bruce A. Shaner - For: Evans Products - April/May 1965 - M 29-65

Set square stake from which a:

30" D.Fir, orig. BT, with scribes visible, bears N.29°E., 8.0 ft.

20" D.Fir, orig. BT, now missing.

Scribed- 60" D.Fir, bears S.10°E., 71.0 ft. "T24S R1W S30 BT"

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Aug. 1966 - C.S. File 52/42-45

Found BTS as recorded by Shaner as follows:

Orig. 30" Fir N.29°E., 8.0 ft., alive, face pitched over.

60" D.Fir S.10°E., 71.0 ft., scribe visible on pitched face. Alive.

Set Brass cap at cor. mkd: County Surveyors Office

T24S	R2W		S 19	R1W	CC
				S 30	
				1966	

We do not mark any new BTs. C C lies approx. 75 ft. E. of new Rock Creek Access Road in rock fill.

Fd. and tied County Corner in BLM resurvey by Lynn M. Roseberry, under Group #534, Surveyed May 1967 - (DCSO records Vol. 34 Page(s) 14170-71)

BLM resurvey by James E. Jelley and Wayne L. Rogers, Cadastral Surveyors, under Group #1051, surveyed April 1981/Sept. 1982 - (DCSO records Vol. 45 Page(s) 17339-40)

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION C C for Secs. 19 & 30, T24-1

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

(102.26 chs.)
 The orig. Closing cor. of secs. 19 and 30, perpetuated and recorded by Shaner in 1965, further perpetuated and recorded by Tracy in 1966, monumented with an iron post 1 1/4" dia., firmly set, projecting 6" above the ground, with brass cap as mkd. in 1966, from which the remaining original bearing tree
 A Fir 33" dia., bears N.19°E., 12 lks. dist., with fragmentary scribe marks visible on partially healed blaze.
 and a bearing tree mkd. by Shaner:

A Fir 55" dia., bears S.13 3/4°E., 108 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

THIS IS NOW AN AMENDED COR. ADD THE MARKS AM TO THE BRASS CAP.

(102.35 chs.)
 Intersect the E. bdy. of sec. 25, T24S R2W. True point for the closing cor. of secs. 19 and 30
 Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 24 S	T 24 S	
R 2 W	S 19	CC
S 25	S 30	
	R 1 W	
1981		

from which
 A Fir 38" dia., bears N.16°E., 111 lks. dist. mkd. T24S R1W S19 CC BT.
 A Fir 4" dia., bears S.36°E., 75 lks. dist. mkd. X BT.
 (From this point, the cor. of secs. 24 & 25 only, T24S R2W, bears N.6°53'E., 8.98 chs.)

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - Debbie Stewart, crew - Aug. 12, 1981 - C.S. File 61/27-30

Found - DCSO brass cap properly mkd. from 1966. The marks AM were added at a later date than the other marks.

An unrecorded BLM BC, 1981, bears N.89°W., 5.8 ft. Orig. 12" now 34" Fir with opened blaze showing 19/30 BT bears N.19°E., 8.0 ft. (Rec. N.29°E., 7.92 ft.) from DCSO brass cap.

60" now 56" Fir with healed over blaze bears S.10°E., 71.8 ft. from DCSO brass cap.

The orig. 12" now 34" Fir with opened blaze showing 19/30 BT, bears N.47°E., 11.54 ft. from BLM cap.

60" now 56" Fir with healed over blaze bears S.15°E., 74.1 ft. from BLM cap.

(Cont. Next Page)

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 700271

PRIMARY CORNER DESCRIPTION C C for Secs. 19 & 30, T24-1

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Unrecorded 38" Fir recently scribed "T24S R1W S19
BT" bears N.30°E., 73.6 ft. This tree is blocked
from DCSO cap by Orig. BT.
(1981-82 BLM resurvey recorded with DCSO after this cor.
visit - see above)