

PRIMARY CORNER DESCRIPTION Sec Cor for 13 & 24 only (East)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 7 Page(s) 2875) and duplicate Pg. 2763)

Set Cedar post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 213, 18, 19 and 24, marked T24S S18 on NE.; R1W S19 on SE.; R2W S24 on SW.; and S13 on NW. faces, with 3 notches on N. and S. edges, from which
A Fir 24" dia., bears N.10°E., 20 lks. dist. mkd. T24S R1W S18 BT.
A Fir 12" dia., bears S.43°E., 21 lks. dist. mkd. T24S R1W S19 BT.
A Fir 18" dia., bears S.46°W., 41 lks. dist. mkd. T24S R2W S24 BT.
A Fir 12" dia., bears N.31°W., 10 lks. dist. mkd. T24S R2W S13 BT.

GLO survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO rec. Vol. 7 Page 2941)

The Sec. cor., which is a post, 2 ft. above ground, marked and witnessed as described by the Surveyor General. This line being incorrect in position and alinement, I reestablish this cor. at the same point, as follows:
Set a Fir post 4 ft. long, 4" sq., 24 ins. in the ground for cor. of secs. 13 and 24, marked T24S S24 on SW.; and R2W S13 on NW. faces, with 3 notches on N. and S. edges, from which
A Fir 18" dia., bears S.46°W., 41 lks. dist. mkd. T24S R2W S24 BT.
A Fir 12" dia., bears N.31°W., 10 lks. dist. mkd. T24S R2W S13 BT.

Survey by Bruce A. Shaner - For: Evans Products Co. - April/May 1965 - M 29-65

Set Square post from which a:
12" D.Fir snag, orig. BT, with bark scribes visible, bears N.31°W., 6.6 ft.
24" D.Fir, orig. BT, with a bark scribe visible, now a blown down tree, bears S.46°W., 27.0 ft.
New BTs-
20" D.Fir, I scribed "T24S R2W S24 BT", bears N.88°W., 36.7 ft.
36" D.Fir, scribed "T24S R2W S18 BT" bears N.7°E., 11.3 ft
15" D.Fir, I scribed "T24S R2W S13 BT", bears N.15°W., 30.1 ft.

(Cont. Next Page)

TOWNSHIP 24 RANGE 02 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Sec Cor for 13 & 24 only (East)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
Aug. 1966 - C.S. File 52/42-44

Found stumps only of BTs recorded by Shaner. Corner falls on
rock face of cut bank.

Set WITNESS CORNER 30 ft. West, as follows:

Set Brass cap at cor. mkd: County Surveyors Office
T 24 S Wit. Cor.
R2W S 13 | R1W
S 24 |
30' E. to Cor.
1966

New BTs- 20" D.Fir N.30½°W., 30.0 ft. mkd. W.C. T24S R2W S13
CS BT.

14" D.Fir S.62°W., 87.6 ft. mkd. W.C. T24S R2W S24
CS BT.

This witness corner lies 25 ft. West of top of cut bank of
new Rock Creek Access Road.