

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 100229

PRIMARY CORNER DESCRIPTION E. 1/4 cor. for Sec. 25 only, T24-4

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GLO survey by Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records Vol. 7 Page(s) 2964-65)

-----  
Set Chittim post 3 ft. long, 3" sq., 24" in ground for 1/4 sec.cor. marked 1/4 S on W. face, from which

A Hemlock 12" dia., bears S.40°E., 14 lks. dist. mkd. 1/4 S BT.

A Chinquapin 8" dia., bears S.45°30'W., 35 lks. dist. mkd. 1/4 S BT.

BLM Resurvey by Norman D. Price, Cadastral Engineer, under Group #242, Surveyed June/Aug. 1950 - (DCSO records Vol. 27 Page(s) 11463)

-----  
Point for the 1/4 sec. cor. of sec. 25, T24S R4W., at midpoint on the E. bdy. of sec. 25.

Set an iron post 3 ft. long, 1" dia., 4" in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.

\*  
1/4 S 25\*

\*  
1950

from which

A Fir 12" dia., bears N.9 1/2°W., 29 lks. dist. mkd. 1/4 S25 BT.

A Fir 14" dia., bears S.63°W., 104 lks. dist. mkd. 1/4 S25 BT.

David Edwards - For: Seneca Jones Timber Co. - March 2014 - C.S. File 65/81-10

-----  
Found - BLM brass cap.

35" Fir N.9 1/2°W., 19.1 ft. with healed blaze.

New - 6" dia., fir scribed "T24S R4W 1/4 S25 BT" bears N.88°W., 18.9'

6 ft. steel post is set 2' north.