

PRIMARY CORNER DESCRIPTION Sec cor for 19 & 30 only, (West)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records Vol. 7 Page(s) 2966)

Set chittim post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 13, 18, 19 and 24, marked T24S S18 on NE.; R3W S19 on SE.; R4W S24 on SW.; S13 on NW. faces, with 3 notches on N. and S. edges, from which

A Fir 18" dia., bears N.38°E., 74 lks. dist. mkd. T24S R3W S18 BT.

A Fir 20" dia., bears S.53°E., 11 lks. dist. mkd. T24S R3W S19 BT.

A Fir 24" dia. S.40°W., 42 lks. dist. mkd. T24S R4W S24 BT

A Fir 10" dia. N.15°W., 60 lks. dist. mkd. T24S R4W S13 BT
(See Vol. 7 Page 2965 fir Wheeler's corner for 19, 24, 25 and 30)

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #658 dated May 21, 1896 (DCSO records Vol. 7 Page(s) 3056)

Intersect E. bdy. of Tp. 23.42 chs. S. of cor. of secs. 19, 24, 25 and 30, which is a Cedar post 24" high, 4" sq., firmly set, mdk. and witnessed as described by the surveyor general, except the NW. & NE. witness trees were blazed but not mkd.

BLM Resurvey by Norman D. Price, Cadastral Engineer, under Group #242, Surveyed June/Aug. 1950 - (DCSO records Vol. 27 Page(s) 11464)

The cor. of secs. 19 and 30, the position of which is determined by using the Wheeler record measurements from the bearing trees his corner of secs. 13, 18, 19 and 24. The cor. of secs. 19 and 30 was utilized for control by Thiel in 1897, who identified this orig. corner when the post was intact and in position, and Thiel changed the call for same to the cor. of secs. 19 and 30; from which the original Wheeler bearing trees are as follows:

A Fir 16" dia., bears N.17½°E., 74 lks. dist. mkd. T24S R3W S18 BT, beneath 67 years overgrowth. (Rec. brg. N.38°E.) I add the scribe marks S19 on the old blaze of this bearing tree.

A Fir 31" dia., bears S.57½°E., 11 lks. dist. mkd. T24S 19 BT beneath 67 years overgrowth. (Rec. brg. S.53°E.)

I add the scribe marks S30 on the old blaze of this BT.

A decayed Fir stump, flush with surface of ground, 36" dia., bears S.48½°W., 42 lks. dist. (Rec. brg. S.40°W.)

A Fir 12" dia., bears N.54½°W., 60 lks. dist. mkd. R4W 24 BT beneath 67 years overgrowth. (Rec. brg. N.15°W.)

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec Cor for 19 & 30 only, (West)

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

At the corner point
 Set an iron post, 3 ft. long, 2" dia., 28" in the ground,
 with brass cap mkd:

| | |
|--------|--------|
| T 24 S | T 24 S |
| R 4 W | S 19 |
| S 24 | S 30 |
| | R 3 W |
| | 1950 |

Douglas Co. Surveyors Office - L.E. Monrean, Deputy - T. Plouff, witness - Nov. 17, 1981 - C.S. file 61/29-24

 Found - 2" I.P. with BLM brass cap properly mkd., protruding 1 ft. above ground.
 16" Fir now a stump with scar visible in growth rings, bears N.17½°E., 48.8 ft. to face, 49.7 ft. to center. This stump is 20" in dia.
 31" Fir now a 31" stump about 5 ft. high with partially healed, pitched over blaze, bears S.57½°E., 6.2 ft. (Rec. 7.3 ft.)
 No other BTs found. SW BT decayed during 1950 resurvey; NW. BT position located in newly logged area.
 New BTs- 9" W.Fir double blaze and scribed "T24S R4W S24 CS BT" bears N.9½°W., 8.2 ft.
 6" W.Fir double blazed and scribed "S19 CS BT" bears N.70°E., 64.9 ft.
 8" W.Fir double blazed and scribed "T24S R4W S30 CS BT", bears S.66°E., 47.0 ft.
 New B.O- Set bridge spike in 48" Red Cedar stump, 2 ft. high, stamped "BO", bears S.13½°E., 14.6 ft.
 Corner lies approx. 15 ft. North of E-W cutting line in a logged area.