

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 24 only, T24-4

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records Vol. 7 Page(s) 2965)

-----  
Set Hemlock post 3 ft. long, 3" sq., 24" in the ground for ¼ sec.cor. mkd. ¼ S on W. face, from which  
A Fir 6" dia., bears N.65°E., 13 lks. dist. mkd.¼ S BT.  
A Maple 12" dia., bears N.85°W., 7 lks. dist. mkd. ¼ S BT.

BLM Resurvey by Norman D. Price, Cadastral Engineer, under Group #242, Surveyed June/Aug. 1950 - (DCSO records Vol. 27 Page(s) 11465)

-----  
Point for the ¼ sec. cor. of secs. 24, at midpoint on the E. bdy. of sec. 24.  
Set an iron post 3 ft. long, 1" dia., 28" in the ground with brass cap mkd. ¼ S 24 |  
1950  
from which  
A Maple 6" dia., bears S.6°W., 57 lks. dist. mkd. ¼ S24 BT.  
A Fir 14" dia., bears N.88°45'W., 41 lks. dist. mkd. ¼ S24 BT.

Douglas Co. Surveyors Office - L.E. Monrean, Deputy - T. Plouff, witness - Nov. 17, 1981 - C.S. File 61/29-30

-----  
Found - BLM brass cap, properly stamped, protruding 10" above the ground.  
6" Maple now 9", with well healed blaze bears S.11½°W., 40.7 ft. (Rec. S.6°W., 37.6 ft.)  
14" Fir now 22" stump, 6 ft. high with well healed blaze bears N.88 ¾°W., 27.1 ft.  
New Accessories:  
5" Hemlock bears N.7°W., 50.7 ft. blazed an X on tree trunk, blaze and scribe "BT" near base.  
Set a RR spike in outer pitch ring of a 46" Fir stump, 2 ft. high, stamped "BO" bears S.35½°W., 66.8 ft.  
Corner lies on a steep North slope, in logged unit, 600 ft. South of cut line corner. (Sketch in File)