

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19 only, (West)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records Vol. 7 Page(s) 2967)

Set Chittim post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 7, 12, 13 and 18 mkd. T24S S7 on NE.; R3W S18 on SE.; R4W S13 on SW.; S12 on NW. faces with 2 notches on N. and 4 notches on S. edges, from which

A Fir 24" dia., bears N.20°E., 33 lks. dist. mkd. T24S R3W S7 BT.

A Fir 20" dia., bears S.61°E., 8 lks. dist. mkd. T24S R3W S18 BT.

A Fir 20" dia., bears S.29°W., 33 lks. dist. mkd. T24S R4W S13 BT.

A Fir 18" dia., bears N.72°W., 45 lks. dist. mkd. T24S R4W S12 BT.

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #658 dated May 21, 1896 (DCSO records Vol. 7 Page(s) 3058)

Intersect E. bdy. of Tp., 270 lks. N. of cor. of secs. 13, 24, 18 and 19, which is a chittim post, 2 ft. high, 4" sq., firmly set, mkd. and witnessed as described by the surveyor general.

BLM Resurvey by Norman D. Price, Cadastral Engineer, under Group #242, Surveyed June/Aug. 1950 - (DCSO records Vol. 27 Page(s) 11465-66)

The corner of secs. 18 and 19, the position of which is determined by using the Wheeler record measurements from his bearing trees at his corner of secs. 7, 12, 13 and 18. The corner of secs. 18 and 19 was utilized for control by Thiel in 1897, who identified this original corner when the post was intact and in position, and Thiel changed the call for same to the cor. of secs. 18 and 19; from which the original bearing trees are as follows:

A Fir 38" dia., dead and down, bears N.20°E., 33 lks. dist. mkd. R 3 S 7 BT.

A Fir 42" dia., bears S.54°E., 8 lks. dist. mkd. T24S R3W S18 BT beneath 67 years overgrowth. (Rec. brg. S.61°E.)

A Fir 38" dia., bears S.22½°W., 33 ks. dist. mkd. on bark T24S S13 BT. (Rec. brg. S.29°W.)

A stump hole bears N.72°W., 45 lks. dist.

At the corner point

(Cont. Next Page)

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 100400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 18 & 19 only, (West)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set an iron post 3 ft. long, 2" dia., 28" in the ground, with
brass cap mkd.

T 24 S	T 24 S
R 4 W	S 18
S 24	S 19
	R 3 W
	1950

from which

A Fir 28" dia., bears N.53¼°E., 96 lks. dist., mkd. T24S
R3W S18 BT.

A Hemlock 11" dia., bears S.23°E., 25 lks. dist. mkd. T24S
R3W S18 BT.

Fd. OK, Oct. 9, 1985 by R. Geisler - C.S. File 63/22-10