

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Sec Cor for 7 & 18 only, (West)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

(See Vol. 7 Pg. 2967 for Wheeler GLO survey. BTs described are now used for the Sec. cor. for 18 and 19, T24-3.)

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #658 dated May 21, 1896 (DCSO records Vol. 7 Page(s) 3060)

Intersect E. bdy. of Tp., 445 lks. N. of cor. of secs.12, 13, 18 and 7, which is a Chittem post 2 ft. high, 4" sq., firmly set, mkd. and witnessed as described by the surveyor general.

BLM Resurvey by Norman D. Price, Cadastral Engineer, under Group #242, Surveyed June/Aug. 1950 - (DCSO records Vol. 27 Page(s) 11467-68)

Point for the cor. of secs. 7 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post 3 ft. long, 2" dia., 29" in the ground with brass cap mkd

T 24 S	T 24 S
R 4 W	S 7
S 13	S 18
	R 3 W
	1950

from which

A Fir 30" dia., bears N.35½°E., 104 lks. dist. mkd. T24S R3W S7 BT.

A Cedar 20" dia., bears S.85°E., 93 lks. dist. mkd. T24S R3W S18 BT.

The sec. corner is located on the East shoulder of a graded dirt logging road.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy; M. Stone, crew - May 1963 - C.S. File 53/9-120

Found - Brass cap set in 1950. Corner is on high mound in center of logging road.

24" dead Cedar snag, S.85°E., 61.4 ft., shows good scar.

Fir stump N.35½°E., 68.6 ft., is almost completely buried in road fill.

New BTs- 14" R.Cedar N.33°E., 103.8 ft. mkd. T24S R3W S7 CS BT.

6" D.Fir S.39½°E., 69.2 ft. mkd. T24S R3W S18 CS BT

Survey by Ronald Geisler, LS #1988 - For: International paper Co. - Oct. 25, 1985 - C.S. File 63/22-8

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec Cor for 7 & 18 only, (West)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Found - 1950 BLM 2½" brass cap on a 2" I.P. extending 14" above ground.
22" Cedar snag bears S.82°E., 62.22 ft. (Rec. S.85°E., 61.38 ft.), scribing partially visible.
New BTs- 16" Fir bears S.38°E., 69.2 ft. scribed T24S R3W S18 BT.
14" Fir bears N.59°E., 77.2 ft. scribed T24S R3W S7 BT.

BLM resurvey by George M. Winter, Cadastral Surveyor under Group No. 2656, surveyed Sept./Nov. 2012 - (DCSO records Vol. 58 Page(s) 23004)

The cor. of secs. 7 & 18 only, on the W. bdy. of T24S R3W perpetuated by Godfrey, in 1963, further perpetuated by Geisler, in 1985, monumented with an iron post, 2" dia., firmly set, projecting 16" above ground, with brass cap (properly) mkd.
from which the remains of a BT mkd. by Price in 1950

A sawed, decayed cedar stump, 26" dia., bears S.85°E., 61.4 ft., with no marks visible.
and the remains of bearing trees mkd. by Godfrey
A cedar, 24" dia., bears N.33¼°E., 103.1 ft., with a healed blaze.
A sawed, decayed fir stump, 19" dia., bears S.38¼°E., 68.9 ft., with a healed blaze.
and a bearing tree mkd. by Geisler
A fir, 28" dia., bears N.59½°E., 77.9 ft., with a healed blaze.
and a new bearing tree
A cedar, 13" dia., bears S.48¼°E., 55.3 ft., mkd. T24S R3W S18 BT.
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.
Corner is located 21 ft. W. of a gravel road, 14 ft. wide, bears N.5°W. and S.5°E.