

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 7 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

BLM Resurvey by Norman D. Price, Cadastral Engineer, under Group #242, Surveyed June/Aug. 1950 - (DCSO records Vol. 27 Page(s) 11469)

Point for the ¼ sec. cor. of sec. 7, T24S R3W, at midpoint on the W. bdy. of sec. 7.
Set an iron post 3 ft. long, 1" dia., 28" in the ground with brass cap mkd. *¼ S 7
1950

from which
A Fir 32" dia., bears N.50°E., 35 lks. dist. mkd. ¼ S7 BT.
A Cedar 16" dia., bears S.67°E., 4 lks. dist. mkd. ¼ S7 BT

BLM resurvey by George M. Winter, Cadastral Surveyor under Group No. 2655, surveyed July/Oct. 2012 - (DCSO records Vol. 58 Page(s) 23014)

The ¼ sec. cor. of sec. 7 only, on the W. bdy. of the Tp., monumented with an iron post, 1" dia., firmly set, projecting 13" above ground, with brass cap (properly) mkd.
from which the remains of bearing trees mkd. by Price in 1950
A sawed fir stump, 47" dia., bears N. 50° E., 23.1 ft., with a healed blaze.
A cedar, 23" dia., bears S.67°E., 2.6 ft., with a healed blaze.
and a new bearing tree
A fir, 5" dia., bears N.52¾°E., 18.4 ft., mkd. X BT.
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.
Corner is located on line with the remains of an old fence line, bears S.