

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 100546

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 12 only, T24-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records Vol. 7 Page(s) 2967-68)

-----  
Set a Dogwood post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S on W. face, from which  
A Chinquapin 6" dia., bears S.84°W., 33 lks. mkd. ¼ S BT.  
A Dogwood 6" dia., bears S.46°E., 32 lks. mkd. ¼ S BT.

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #658 dated May 21, 1896 (DCSO records Vol. 7 Page(s) 3075)

-----  
We again failed to find any marks of a ¼ sec. cor. or its bearing trees.

BLM Resurvey by Norman D. Price, Cadastral Engineer, under Group #242, Surveyed June/Aug. 1950 - (DCSO records Vol. 27 Page(s) 11469)

-----  
Point for the ¼ sec. cor. of sec. 12, T24S R4W., at midpoint on the E. bdy. of sec. 12.  
Set an iron post 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd. ¼ S 12|  
1950  
from which  
A Hemlock 20" dia., bears N.50½°W., 46 lks. mkd. ¼ S12 BT.  
A Cedar 16" dia., bears S.64°W., 82 lks. mkd. ¼ S12 BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy; M. Stone - June 14, 1963 - C.S. File 53/9-103

-----  
Found - GLO brass cap at corner set in 1950 resurvey.  
20" Red Cedar S.64°W., 54.1 ft., all scribing "¼ S12 BT" visible in not yet healed over blaze, tree alive and in good condition.  
20" Hemlock to the NW. is uprooted, down and dead.  
New BT - 7" Hemlock N.44°W., 45.5 ft. mkd. ¼ S12 CS BT.  
Corner lies on bench near foot of steep SW. slope.

BLM resurvey by George M. Winter, Cadastral Surveyor under Group No. 2655, surveyed July/Oct. 2012 - (DCSO records Vol. 58 Page(s) 23014-5)

-----  
The ¼ sec. cor. of sec. 12 only, T24S R4W on the W. bdy. of the Tp., perpetuated by Godfrey, in 1963, monumented with an iron post, 1" dia., firmly set, projecting 15" above ground supported in a mound of stone, 3 ft. base, 1 ft. high, with brass cap (properly) mkd.  
continued next page

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 100546

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 12 only, T24-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of a BT mkd. by Price in 1950  
A sawed cedar stump, 32" dia., bears S.64°W., 54.5 ft.,  
with no marks visible.  
and remains of a bearing tree mkd. by Godfrey  
A sawed decayed hemlock stump, 26" dia., bears N.44°W.,  
45.5 ft., with a healed blaze.  
and new bearing trees  
A fir, 16" dia., bears S.0¾°W., 8.4 ft., mkd. ¼ S12 BT.  
A fir, 4" dia., bears N.83°W., 25.8 ft., mkd. X BT.  
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail)  
driven at the base right side-center.