

PRIMARY CORNER DESCRIPTION Sec Cor for 6 & 7 only, (West)

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records Vol. 7 Page(s) 2968)

 Set Yew post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 1, 6, 7 and 12, marked T24S S6 on NE.; R3W S7 on SE.; R4W S12 on SW.; S1 on NW. faces, with 1 notch on N. and 5 notches on S. edges, from which

- A Fir 18" dia., bears N.55°E., 15 lks. dist. mkd. T24S R3W S6 BT.
- A Fir 18" dia., bears S.21°E., 100 lks. dist. mkd. T24S R3W S7 BT.
- A Fir 16" dia., bears S.25°W., 17 lks. dist. mkd. T24S R4W S12 BT.
- A Fir 20" dia., bears N.84°W., 24 lks. dist. mkd. T24S R4W S1 BT.

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #658 dated May 21, 1896 (DCSO records Vol. 7 Page(s) 3062)

 Intersect E. bdy. of Tp. 624 lks. N. of cor. of secs. 1, 12, 6 and 7 which is a Yew post 2 ft. high, 4" sq., firmly set, marked and witnessed as described by the surveyor general.

BLM Resurvey by Norman D. Price, Cadastral Engineer, under Group #242, Surveyed June/Aug. 1950 - (DCSO records Vol. 27 Page(s) 11469-70)

 Point for the cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post 3 ft. long, 2" dia., 28" in the ground with brass cap mkd.

T 24 S	T 24 S
R 4 W	S 6
S 12	S 7
	R 3 W
	1950

from which

- A Fir 36" dia., bears N.68°E., 45 lks. dist. mkd. T24S R3W S6 BT.
- A Fir 36" dia., bears S.62°45'E., 73 lks. dist. mkd. T24S R3W S7 BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy; M. Stone, crew - Feb/March 1963 - C.S. File 53/9-1

 Found - GLO brass cap dated 1950.
 (Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec Cor for 6 & 7 only, (West)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

36" Fir N.68°E., 29.7 ft., recent blowdown, scribing visible on not healed over scar.
36" Fir S.62°45'E., 48.2 ft., recent blowdown, face pitched over, scribe marks not readily visible.
New BTs- 19" Red Cedar N.36°E., 20.5 ft. mkd. T24S R3W S6 CS BT.
(?) D.Fir S.45°E., 63.7 ft. mkd. T24S R3W S7 CS BT.

J.E. Shaw - Weyerhaeuser Co - April 28, 1966 - C.S. 53/111-30

Found - 1950 brass cap in good condition.
Orig. 36" Fir, N.68°E., 45 lks., but windthrown.
Orig. 36" Fir S.62°45'E., 73 lks., but windthrown.
16" Cedar BT, N.38½°W., 19.3 ft., with scribing visible.
16" Fir, S.45°E., 63.7 ft., with scribing visible.
40" Fir N.67°E., 28.4 ft., tags on windthrown tree.
40" Fir S.64°E., 36.5 ft., tags on windthrown tree.
New - 16" Cedar N.38½°W., 19.3 ft. "W" nail/plate and brass disc.
14" Hemlock S.23°W., 19.6 ft. with "W" nail/plate and brass disc.

Fd. OK, DCSO, April 1967

BLM resurvey by George M. Winter, Cadastral Surveyor under Group No. 2655, surveyed July/Oct. 2012 - (DCSO records Vol. 58 Page(s) 23015-6)

The cor of secs 6 & 7 only, on the W bdy of the Tp perpetuated by Godfrey, in 1963, further perpetuated by Shaw, in 1966, monumented with an iron post, 2" dia., firmly set, projecting 12" above ground, with brass cap (properly) mkd. from which the remains of a BT mkd. by Price in 1950
A sawed, decayed fir stump, 40" dia., bears S.62¼°E., 48.2 ft., with scribe marks T 4S R3W S7B visible on an open blaze.
and remains of bearing trees mkd. by Godfrey
A cedar, 33" dia., bears N.36°E., 20.5 ft., with a healed blaze.
A decayed fir snag, 18" dia., bears S.45°E., 63.7 ft., with illegible marks visible on a partially healed blaze.
and remains of a bearing tree mkd. by Shaw
A decayed hemlock snag, 24" dia., bears S.23°W., 19.6 ft. with stamped aluminum tag visible in a partially healed blaze.
continued next page

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Sec Cor for 6 & 7 only, (West)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

and a new bearing tree

A fir, 14" dia., bears S.74½°E., 42.2 ft., mkd. T24S R3W
S7 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail)
driven at the base right side-center.

Corner is located 124 ft. N. of a gravel road, 14 ft. wide,
bears S.65°E. and N.70°W.

NAD 1983 (2011)

Latitude: 43°30'12.33"N. Longitude: 123°06'28.21"W.