

PRIMARY CORNER DESCRIPTION Center West 1/16 Sec. 31

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey by Wm. W. Glenn, Cadastral Surveyor, under Group #416, surveyed Sept/Oct 1958 - (DCSO records Vol. 30 Page(s) 12601)

Point for the center W 1/16 sec. cor. of sec. 31
Set an iron post, 28" long, 2½" dia., 26" in the ground, with brass cap marked:

C W 1/16 C
S31
1958

from which

- A fir, 55" dia., bears N.20¼°W., 241 lks., mkd: CW 1/16 S31 BT.
- A fir, 35" dia., bears S.57°W., 257½ lks., mkd: CW 1/16 S31 BT.

Mark Smalley, For Roseburg Forest Products - Crew: William Olson & Niel Danko - May 2009 - C.S. File 65/66-23

-
- Found - 71" D.Fir, N.20¼°W., 159.1', healed face.
35" Fir, S.57°W., 257.7 lks. gone, 1958
1958 BLM Brass cap (properly marked)
 - New - 12" D.Fir N.79°E., 47.8' measured to a nail in the side-center of stump scribed "CW 1/16 BT" with LS 2354 brass washer.
Declination 18°

Ken Hoffine, Lone Rock Timberland Co. - Crew: Gary Angiolet & Ignacio Roman - Nov. 2009 - M160-17

-
- Found - 1958 BLM brass cap.
71" D.Fir bears N.20¼°W., 157.8 ft. (rec. N.20¼°W., 159.06 ft) healed face & BLM tag.
12" D.Fir N.83°E., 47.7' ft. (rec. N.79°E., 47.8 ft) visible scribing and tag.
 - Note - Corner lies on open grass covered, rocky north facing slope. Metal fence post approx. 1.5 ft. NE of corner. Old fence corner with fence running south and west bears N.59°E., 36'.

Douglas Co. Surveyor's Office - Crew: Stephen Flause & Mike Koch - 7/12/2016 - C.S. File 67/44-20

-
- Condition report only
 - Found - A 2½" dia. Iron post by Glenn, 1958, firmly set, projecting 2" above the ground with a 3¼" brass cap (properly) marked.
- continued next page

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 120140

PRIMARY CORNER DESCRIPTION Center West 1/16 Sec. 31

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BTs by Glenn in 1958 -

A 47" dia. x 4' tall sawn fir stump bears S.57°W.,
166.7 ft. I opened to reveal scribing "CW 1/16".
(Rec. S.57°W., 170.0 FT.)

A 72" dia. D.Fir bears N.20¼°W., 157.8 ft. with a
healed blaze.

A BT by Smalley in 2009 per C.S. 65/66-23 -

An 18" dia. D.Fir bears N.84°E., 47.8 ft. with a
healed single blaze. (Rec. N.79°E.)

Location & comments - All BTs have BT tags attached. All
new BTs have double blazed faces with bearings
measured to the center of the tree at the root
crown and distances measured to the side and
center of the root crown.

The monuments falls on moderate grass covered SW
slope with old growth fir forest north & young
reprod. Fir in the sw quadrant.

See sketch map in attached notes.

Compass declination: 15° E.