

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 30 & 31

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #152, dated June 3, 1871 - (DCSO records Vol. 7 Page(s) 2958)

Set ¼ sec. post from which
A fir, 8" dia., bears S.50°W., 15 lks.
A fir, 9" dia., bears N.60°E., 25 lks.

BLM dependent resurvey by Wm. W. Glenn, Cadastral Surveyor, under Group #416, surveyed Sept/Oct 1958 - (DCSO records Vol. 30 Page(s) 12598)

Point for the ¼ sec. cor. of secs. 30 & 31, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 26" in the ground with brass cap marked:
T24S R3W
¼ $\frac{S\ 30}{S\ 31}$
1958

from which
A hemlock, 18" dia. bears N.35½°W., 49½ lks. mkd: ¼ S30 BT
A hemlock, 25" dia., bears S.36½°E., 60 lks. mkd: ¼ S31 BT

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - E. West - Sept. 1967 - C.S. File 54/27-90

Found - 1958 Cadastral brass cap, properly mkd., buried under limbs & dirt.
18" Hemlock, alive, N.35½°W., 32.6 ft., scribe visible on unhealed blaze.
SE BT, now stump.
New BT - 7" Cedar S.4°E., 35.5 ft. mkd. "¼ S31 CS BT"
Note - This corner lies on steep NE slope, approx. 85 ft. W of Jeffers Creek.

David Edwards - For: Seneca Jones Timber Co. - Feb. 2012 - C.S. File 65/75-2

Found - BLM brass cap.
A 24" dia., Hemlock stump bears N.35½°W., 32.6 ft.
A 25" cedar with curved trunk leaning east bears S.4°E., 35.9 ft. with healed blaze.
New - A 13" dia., hemlock scribed "¼ S30 BT" bears N.61°W., 22.5 ft.
Set 6 ft. steel post 2 ft. West.