

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #152, dated June 3, 1871 - (DCSO records Vol. 7 Page(s) 2959-60)

Set ¼ sec. post from which
A fir, 8" dia., bears N.5°W., 8 lks.
A fir, 10" dia., bears S.30°E., 12 lks.

BLM dependent resurvey by Norman D. Price, Cad. Engineer, under Group 242 surveyed June/Aug. 1950 (DCSO recs. Vol. 27 Page(s) 11483)

Point for the ¼ sec. cor. of secs. 19 & 30, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:
¼ $\frac{S\ 19}{S\ 30}$
1950

from which
A W.Fir, 14" dia., bears N.46°45'W., 50 lks., mkd: ¼ S19 BT.
An I.Cedar, 28" dia., bears S.1°45'E., 38 lks., mkd: ¼ S30 BT.

FD. BC & BTs - Douglas Co. Surveyors Office - Vernon "Ray" Tracy Aug. 1967 - C.S. File 54/27-81

Rob Ward, Ward NW Inc. - For: Seneca Jones CO. - 12/2001 - M139-34

Found - 2½" GLO brass cap dated 1950 with the following accessories:
60" D.Fir stump (not of rec.) bears N.22°E., 11.0 ft. to a 60D nail in top of stump.
30" I.Cedar stump bears S.1°45'E., 38 lks., rotten face.
New BT - 10" R.Cedar bears N.26°W., 25.7 ft. scribed "¼ S19 BT"
18" Hemlock bears N.81°W., 17.1 ft. scribed "¼ S30 BT"