

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 7 Page(s) 3013-4)

Set hemlock post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. marked ¼ sec. cor. mkd. ¼ S on N face from which
A hemlock, 18" dia., bears N.21°W., 35 lks., mkd: ¼ S BT.
A hemlock, 18" dia., bears S.62°E., 40 lks., mkd: ¼ S BT.

BLM dependent resurvey by Norman D. Price, Cad. Engineer, under Group 242 surveyed June/Aug. 1950 (DCSO recs. Vol. 27 Page(s) 11489)

Point for the ¼ sec. cor. of secs. 7 & 18, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:
¼ $\frac{S \ 7}{S \ 18}$
1950

from which
A I.Cedar, 46" dia., bears N.3¼°W., 31 lks., mkd: ¼ S7 BT.
A Yew, 6" dia., bears S.31°E., 28 lks., mkd: ¼ S18 BT.

Fd. Ok by R. Geisler, 10/25/1985 - C.S. File 63/22-4