

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 6 & 7

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 7 Page(s) 3017)

Set yew post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. marked ¼ sec. cor. mkd. ¼ S on N face from which

- A fir, 20" dia., bears N.10°W., 72 lks., mkd: ¼ S BT.
- A fir, 18" dia., bears S.37°W., 60 lks., mkd: ¼ S BT.

BLM dependent resurvey by Norman D. Price, Cad. Engineer, under Group 242 surveyed June/Aug. 1950 (DCSO recs. Vol. 27 Page(s) 11491)

Point for the ¼ sec. cor. of secs. 6 & 7, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

¼ $\frac{S\ 6}{S\ 7}$
1950

from which

- A fir, 22" dia., bears N.49°W., 73 lks., mkd: ¼ S6 BT.
- A fir, 26" dia., bears S.74°W., 72 lks., mkd: ¼ S7 BT.

BLM resurvey by George M. Winter, Cadastral Surveyor under Group No. 2655, surveyed July/Oct. 2012 - (DCSO records Vol. 58 Page(s) 23021)

The ¼ sec. cor. of secs. 6 & 7, perpetuated by Peel, in 1979, monumented with an iron post, 1" dia., firmly set, projecting 7" above ground, with brass cap (properly) mkd. from which the remains of a BT mkd. by Price in 1950

- A sawed, decayed fir stump, 37" dia., bears N.52½°W., 48.2 ft., with a healed blaze. (Record, N.49°W.)

and a bearing tree mkd. by Peel

- A fir, 28" dia., bears S.63¼°W., 20.0 ft., with a healed blaze.

and a new bearing tree

- A fir, 6" dia., bears N.59½°W., 34.1 ft., mkd. ¼ S6 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.