

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 140700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 6; & 31, T23-3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by James P. Currin, Deputy Surveyor, under Contract #438, dated May 2, 1882 - (DCSO records Vol. 5 Page(s) 2211)

Set a post 4 ft. long, 4" sq., 24" in the ground on S. slope in open timber for 1/4 sec. cor. marked 1/4 on N. face, from which
A Maple 4" dia., bears South 25 lks. mkd. 1/4 S BT.
A Maple 4" dia., bears N.10°E., 35 lks. dist. mkd. 1/4 S BT.

BLM Resurvey by Norman D. Price, Cadastral Engineer - under Group #242 - Surveyed June/Aug. 1950 - (DCSO records Vol. 27 Page(s) 11459)

Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd:
1/4 $\frac{S\ 31}{S\ 6}$
1950
from which
A Yew 10" dia., bears N.64°45'W., 14 lks. dist., mkd. 1/4 S31 BT.
A Hemlock 10" dia., bears S.16 1/4°E., 19 lks. dist., mkd. 1/4 S6 BT.

Marion D. Hale - For: Weyerhaeuser Company - Nov. 1961 - C.S. File 51/31-2 and 1963 visit, C.S. File 53/107)

Found - GLO resurvey 1950 brass cap.
10" Hemlock S.16 1/4°E., 19 lks. (53/107 says "Yew")
10" Yew N.64 3/4°W., 14 lks.
BTs - 17" Yew N.40°W., 26.1 ft. "W" nail & plate
72" Fir snag S.42°W., 5.3 ft. "W" nail & plate.