

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 160120

PRIMARY CORNER DESCRIPTION SE 1/16 Sec. 31

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Wm. W. Glenn, Cadastral Surveyor, under Group #416, surveyed Sept/Oct 1958 - (DCSO records Vol. 30 Page(s) 12602)

Point for the SW* 1/16 sec. cor. of sec. 31, at intersection with the E & W center line of the SE $\frac{1}{4}$.
Set an iron post, 28" long, 2 $\frac{1}{2}$ " dia., 26" in the ground, with brass cap marked:

SE 1/16 S31

1958

from which

A fir, 22" dia., bears S.60 $\frac{1}{2}$ °E., 41 lks., mkd: SE 1/16 S31 BT.

A cedar, 9" dia., bears N.72 $\frac{1}{2}$ °W., 63 lks., mkd: SE 1/16 S31 BT.

*SE - orig record says SW

Douglas Co. Surveyors Office - Stephen Flause - Mike Koch - July 2016, filed 12/5/2018 - C.S. File 67/45-16

Monument fd ok.

The two BTs are in good condition and agree with record BLM bearings and distances.

The 22" fir is not 35" in dia.

The 9" cedar is now 28" in dia.

Both trees are re-tagged and flagged.