

PRIMARY CORNER DESCRIPTION E 1/16 Secs. 30 & 31

Alias	Description
Alias	Description
Alias	Description
Alias	Description

BLM dependent resurvey by Wm. W. Glenn, Cadastral Surveyor, under Group #416, surveyed Sept/Oct 1958 - (DCSO records Vol. 30 Page(s) 12597)

Point for the E 1/16 sec. cor. of secs. 30 & 31
Set an iron post, 28" long, 2½" dia., 26" in the ground with brass cap marked:

E 1/16 $\frac{S\ 30}{S\ 31}$
1958

from which

- A fir, 8" dia., bears N.2¼°W., 20 lks., mkd: E 1/16 S30 BT
- A fir, 9" dia., bears S.5½°W., 34 lks., mkd: E 1/16 S31 BT

Douglas Co. Surveyor's Office - Crew: Stephen Flause & Mike Koch - 6/16/2016 - C.S. File 67/44-14

Found - A 2½" dia. IP by Glenn, 1958 USBLM, laying loosely on the top of the ground as displaced by an uprooted tree, with 3¼" brass cap (properly) mkd A BT by Glenn in 1958 -

A 14" dia. x 12" tall broken and rotted D.Fir stump bears S.5½°W., 22.4 ft. I opened to find scribe marks "E 1/16 S31 BT" visible on an intact blazed face.

No evidence remains of the 1958 NW BT.

New - The 1958 USBLM monument is reset at record bearing and distance from the original 1958 BT and now projects 3" above the ground. The brass cap has been marked "RESET 2016"

An 18" dia. Hemlock bears N.39¼°E., 17.5 ft. scribed "E 1/16 S30 CS BT".

A 6" dia. D.Fir bears N.60¼°E., 47.9 ft. scribed "E 1/16 S30 CS BT"

Location & comments - All BTs have BT tags attached. All new BTs have double blazed faces with bearings measured to the center of the tree at the root crown and distances measured to the side and center of the root crown.

The corner falls on a steep NNW slope on an E-W timber cutting line with young fir reprod. to the north and old growth fir, hemlock & maple to the south.

Compass declination - 15°E.