

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17, 18, 19, & 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 7 Page(s) 3008)

Set cedar post 4 ft. long, 4" sq. 24" in the ground for cor. to secs. 17, 20, 18, & 19 marked T24S S17 on NE., R3W S20 on SE., S19 on SW., & S18 on NW faces with 3 notches on S & 5 notches on E edges from which

- A fir, 50" dia., bears N.31°E., 45 lks., mkd: T24S R3W S17 BT.
- A hemlock, 5" dia., bears S.14°E., 38 lks., mkd: T24S R3W S20 BT.
- A maple, 7" dia., bears S.71°W., 23 lks., mkd: T24S R3W S19 BT.
- A hemlock, 18" dia., bears N.30°W., 18 lks., mkd: T24S R3W S18 BT.

BLM dependent resurvey by Norman D. Price, Cad. Engineer, under Group 242 surveyed June/Aug. 1950 (DCSO recs. Vol. 27 Page(s) 11484)

Point for the cor. of secs. 17, 18, 19, & 20, proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap marked:

T24S	R3W
<u>S 18</u>	<u>S 17</u>
S 19	S 20
1950	

from which

- An iron post, 3 ft. long, 2" dia., set 28" in the ground, for a reference monument, bears S.45°E., 30 lks., with brass cap mkd: T24S R3W S20 RM 1950 & an arrow pointing to the true cor.
- An iron post, 3 ft. long, 2" dia., set 28" in the ground, for a reference monument, bears N.45°W., 30 lks., with brass cap mkd: T24S R3W S18 RM 1950 & an arrow pointing to the true cor.

Ronald Geisler - For: Champion International - Witnesses: L. Sibley & D. Turner - Oct. 9, 1985 - C.S. File 63/22-11

Found - 1950 BLM brass cap on 2" IP extends 6" above ground. RM to the SE not found.

RM - 2½ brass cap on 2" IP extends 6" above ground & marked with arrow pointing to true corner bears N.45°W., 19.80 ft. from corner.

No record of the following BTs I fd:

13" Chinquapin bears S.25°E., 11.18 ft. (Metal disc in face of tree) continued next page

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17, 18, 19, & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New -	32" stump bears S.43°W., 11.14 ft. (Metal disc in face of tree) 36" snag bears N.77°W., 43.0 ft. (Metal disc in face of tree) 2½" alum. cap on 1"x36" iron pipe extends 5" above ground & marked "LS-1988 1985 RM" with arrow pointing to true corner bears S.45°E., 19.80 ft. from true corner.