TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 7 Page(s) 3011)

Set hemlock post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. marked ¼ sec. cor. mkd. ¼ S on W face from which
A Fir, 20" dia., bears N.38°W., 51 lks., mkd: ¼ S BT.
A hemlock, 12" dia., bears S.73°E., 15 lks., mkd: ¼ S BT.

BLM dependent resurvey by Norman D. Price, Cad. Engineer, under Group 242 surveyed June/Aug. 1950 (DCSO recs. Vol. 27 Page(s) 11486-7)

Point for the ¼ sec. cor. of secs. 17 & 18, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked: ¼
S 18 | S 17
1950
from which
A fir, 22" dia., bears S.49¼°E., 33 lks., mkd: ¼ S17 BT.
A fir, 22" dia., bears N.83¼°W., 67 lks., mkd: ¼ S18 BT.

Fd. Ok by WEYCO 9/1957 - C.S. 42/323 & C.S. 51/31-3

Ronald Geisler - Champion International - 10/9/1985 - C.S. 63/22-6

Found - 1950 GLO brass cap on a 1" IP extends 7" above ground, properly marked.
32" Fir bears S.49¼°E., 21.78 ft. closed face. 1950
26" Fir stump bears N.80½°W., (Rec. N.83¼°W.) 44.63 ft. (Rec. 44.22 ft.) scribing visible. 1950
New BT - 5" Fir bears S.55½°W., 8.17 ft. scribed ¼ S18 BT.

BLM resurvey by George M. Winter, Cadastral Surveyor under Group No. 2655, surveyed July/Oct. 2012 - (DCSO records Vol. 58 Page(s) 23023)

The ¼ sec. cor. of secs. 17 & 18, perpetuated by Geisler, in 1985, monumented with an iron post, 1" dia., firmly set, projecting 9" above ground, with brass cap (properly) mkd. from which the remains of bearings tree mkd. by Price in 1950
A fir, 39" dia., bears S.49¼°E., 21.8 ft. with a healed blaze.
A decayed fir stump, bears N.83¼°W., 44.2 ft., with no marks visible.
and a new bearing tree
A fir, 4" dia., bears N.76¾°W., 33.5 ft., mkd. X BT.