TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 8

Alias Description
Alias Description
Alias Description
Alias Description

GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 7 Page(s) 3014)

---

Set cedar post 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. marked ¼ sec. cor. mkd. ¼ S on W face from which
A cedar, 8" dia., bears N.29°W., 18 lks., mkd: ¼ S BT.
A chinquapin, 10" dia., bears S.32°E., 51 lks. mkd: ¼ S BT

BLM dependent resurvey by Norman D. Price, Cad. Engineer, under Group 242 surveyed June/Aug. 1950 (DCSO recs. Vol. 27 Page(s) 11489)

---

Point for the ¼ sec. cor. of secs. 7 & 8, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 8" in the ground to bedrock, and in a mound of stone, 4½ ft. base, to top, with brass cap marked

¼
S 7|S 8
1950

from which
A cedar, 12" dia., bears S.56½°E., 8 lks., mkd: ¼ S8 BT.
A cedar, 24" dia., bears N.34°45'W., 41 lks., mkd: ¼ S7 BT