

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor Secs 5, 6, 7, & 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCS0 records Vol. 7 Page(s) 3015)

Set Yew post 4 ft. long, 4" sq. 24" in the ground for cor. to secs. 5, 6, 7, & 8 marked T24S S5 on NE., R3W S8 on SE., S7 on SW., & S6 on NW faces with 5 notches on S & E edges from which
A cedar, 18" dia., bears N.39°E., 16 lks., mkd: T24S R3W S5 BT.
A fir, 60" dia. bears S.43°E., 71 lks. mkd: T24S R3W S8 BT
A fir, 10" dia. bears S.30°W., 40 lks. mkd: T24S R3W S7 BT
A hemlock, 20" dia., bears N.30°W., 65 lks., mkd: T24S R3W S6 BT.

BLM dependent resurvey by Norman D. Price, Cad. Engineer, under Group 242 surveyed June/Aug. 1950 (DCS0 recs. Vol. 27 Page(s) 11490)

Point for the cor. of secs. 5, 6, 7, & 8, proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap marked: T24S R3W
S 6 | S 5
S 7 | S 8
1950
from which
A fir, 22" dia., bears N.88°45'E., 40 lks., mkd: T24S R3W S5 BT.
A fir, 54" dia. bears S.45½°E., 9 lks. mkd: T24S R3W S8 BT
A yew, 12" dia. bears S.4½°W., 56 lks. mkd: T24S R3W S7 BT
A cedar, 20" dia., bears N.9½°W., 70 lks., mkd: T24S R3W S6 BT.

BLM resurvey by George M. Winter, Cadastral Surveyor under Group No. 2655, surveyed July/Oct. 2012 - (DCS0 records Vol. 58 Page(s) 23020)

The cor. of secs. 5, 6, 7, and 8, monumented with an iron post, 2" dia., firmly set, projecting 12" above ground, with brass cap (properly) mkd.
from which the remains of bearing trees mkd. by Price in 1950
A fir, 31" dia., bears N.88¾°E., 32.5 ft., with a healed double blaze. (Record, 26.4 ft.)
A sawed, decayed fir stump, 62" dia., bears S.45½°E., 5.9 ft., with axe marks visible.
A roothole bears S.4½°W., 37.0 ft., with fallen yew snag, 15" dia., lying alongside, with no marks visible.
continued next page

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor Secs 5, 6, 7, & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A sawed, decayed cedar stump, 40" dia., bears N.12½°W., 46.2 ft., with a healed blaze. (Record, N.9½°W.)
and new bearing trees
A fir, 10" dia., bears S.59¾°E., 33.9 ft., mkd. T24S R3W S8 BT.
A hemlock, 5" dia., bears S.50¼°W., 27.1 ft., mkd. T24S R3W S7 BT.
A fir, 6" dia., bears N.62½°W., 19.2 ft., mkd. T24S R3W S6 BT.
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, Group No. 2500 Admin file No. 1408, surveyed July/Aug. 2014 - (DCSO records Plat T24-3-2016-1 all info on plat & Vol. 58 Page(s) 23321-2

The cor. of secs. 5, 6, 7, & 8, monumented with an iron post, 2" dia, firmly set, projecting 12" above the ground, with a brass cap (properly) mkd.
from which the remains of BTs mkd. by Price in 1950 and reported by Winter in 2012
A fir, 33" dia, bears N.88¾°E., 32.5 ft., with a healed double blaze.
A decayed fir stump, 62" dia, bears S.45½°E., 5.9 ft., with axe marks visible.
A decayed cedar stump, 40" dia, bears N.12½°W., 46.2 ft., with no marks visible.
and bearing trees mkd. by Winter in 2012
A fir, 10" dia, bears S.57¾°E., 34.9 ft., with scribe marks T24S R3W S8 BT visible on a partially healed blaze. (Record, S.59¾°E., 33.9 ft.)
A hemlock, 5" dia, bears S.50¼°W., 27.1 ft., with scribe marks T24S R3W S7 BT visible on a partially healed blaze.
A fir, 6" dia, bears N.62½°W., 19.2 ft., with scribe marks T24S R3W S6 BT visible on a partially healed blaze.

Brent Knapp - Crew: N. Fromdahl, J. Ogden, & W. Keady - 6/26/2023 - C.S. File 65/111-55

Condition report
Found - Brass Cap (properly mkd)
33" Fir, N.88¾°E., 32.5'; Healed Scar, tag.
62" Decayed Fir stump, S.54½°E., 5.9'; Axe work still visible, tag.
40" Decayed Cedar stump, N.12½°W., 46.2'.
Continued next page

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor Secs 5, 6, 7, & 8

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

10" Fir, S.57¼°E., 34.9'; partially visible scribe, tag.
7" Hemlock, S.50¼°(E) 27.1'; partially visible scribe, tag.
8" Fir, N.62½°W., 19.2; healed blaze, tag.
Steel post, 1' West
Steel Post, 1' North
Note - Compass Declination 15°E