

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 6

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 7 Page(s) 3018)

Set hemlock post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. marked ¼ sec. cor. mkd. ¼ S on W face from which
 A fir, 18" dia., bears N.11°E., 72 lks., mkd: ¼ S BT.
 A fir, 20" dia., bears S.63°W., 14 lks., mkd: ¼ S BT.

BLM dependent resurvey by Norman D. Price, Cad. Engineer, under Group 242 surveyed June/Aug. 1950 (DCSO recs. Vol. 27 Page(s) 11492)

Point for the ¼ sec. cor. of secs. 5 & 6, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

¼
 S 6 | S 5
 1950

from which
 A fir, 10" dia., bears N.77¼°E., 8 lks., mkd: ¼ S5 BT.
 A fir, 9" dia., bears N.32°W., 33 lks., mkd: ¼ S6 BT.

M. Hale, Weyerhaeuser Co. - 2/24/1960 - C.S. File 53/111-10

Found - 1950 brass cap
 9" Fir, N.30°W., 21.7 ft., (rec. N.32°W.) measured to face.
 12" Fir, N.77°E., 4.7 ft., (rec. N.77¼°E., 5.28 ft.) measured to face.

New - 8" Fir, S.36°E., 16.2 ft.
 14" Fir, N.18°W., 18.9 ft.

Note - Ground cover: Sapling, small poles, bracken fern & salal.

Donald Peel - For: Weyerhaeuser, Co. - Oct. 1979 - M80-57

Found - 1" IP with GLO BC 1950
 18" Fir, N.80°E., 4.8'
 11" Fir N.31°W., 22.1'
 21" Fir, N.24°W., 18.9'
 14" Fir, S.36°E., 16.2'] Dist. & brg. to "W" nail

continued next page

1

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 6

Alias	Description
Alias	Description
Alias	Description
Alias	Description

BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, & Robert Browning, Survey Technician, under Group #11739, surveyed July/Oct. 1994 - (DCSO records Vol. 52 Page(s) 20061-2)

The 1/4 sec. cor. of secs. 5 & 6, determined at record bearing & distance from the bearing trees mkd. by Price, after a thorough search was made for Price's iron post, from which the remains of bearing trees mkd by Price:


A fir, 20" dia., bears N.77 1/4°E., 8 lks., with healed blaze.

A sawed fir stump, 11" dia., bears N.32°W., 33 lks., with scribe marks BT visible on opened blaze. and a tree referenced by person(s) unknown & used by Peel, in 1979

A fir, 14" dia., bears S.32 3/4°E., 26 lks., with chaining notch at base of tree.

At the corner point

Set a stainless steel post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd. T24S R3W



BLM Dependent resurvey by Richard J. Dieckmann, Cadastral Surveyor, Group No. 2500 Admin file No. 1408, surveyed July/Aug. 2014 - (DCSO records Plat T24-3-2016-1 all info on plat & Vol. 58 Page(s) 23321-2)

The 1/4 sec. cor. of secs. 5 & 6, monumented with an iron post, 2 1/2" dia, firmly set, projecting 3" above the ground, with a brass cap (properly) mkd.

from which the remains of BTs mkd. by Price in 1950 and reported by Seibold and Browning in 1994

A fir, 20" dia, bears N.77 1/4°E., 5.3 ft., with a healed blaze.

A sawed, decayed fir stump, 11" dia, bears N.32°W., 21.8 ft., with scribe marks BT visible on an opened blaze. and a BT mkd. by Hale, in 1960 and reported by Seibold and Browning in 1994

A fir, 16" dia, bears S.32 3/4°E., 17.2 ft., with axe marks visible. (Record, person(s) unknown) and a BT mkd. by Hale, in 1960

A sawed, decayed fir stump, 24" dia, bears N.24°W., 19.3 ft., with axe marks visible.

and a new bearing tree

A fir, 6" dia, bears N.66°W., 7.8 ft., mkd. 1/4 S6 BT.