

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 240240

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - C.E. Roberts, Co. Surveyor -
May 26, 1903 - FB 7 Pg. 7

Set a sand stone 4"x12"x16"
Alder 8" N.79°E., 78 (lks.?)

A.R. Evans - 1952 - C.S. File 41/100

Corner set by C.E. Roberts in F.B. 7 Pg. 7, this survey was
made mor Tip Hitton, On May 26, 1903.
Found - OBT, an alder
Set - 1½" iron pipe for cor. from which:
14" Cedar bears S.65°E., 33.5 ft.
14" Cedar bears N.53°E., 28.6 ft.

Douglas Co. Surveyors Office - James W. Byron, Deputy -
Witnesses: G. Welker & J. Fee - For: Roseburg Lumber Co. -
Oct. 29, 1956 - M1-18

Found 1½" iron pipe set by A.R. Evans in re-establishing
corner set for midpoint of N & S centerline. C.E. Roberts (FB
7 Pg. 7) based on a BT fd.

Daniel Baker - Weyerhaeuser Co. - 12/15/94 - M 121 - 58 A&B

Set- 1¼"X36" Iron pipe with brass cap dated 1994
28" cedar, N.42°E. 25' scribed "C¼ S29 BT"
11" maple, S.30°E. 14.4' scribed "C¼ S29 BT"
20" cedar, S.8°W. 24' scribed "C¼ S29 BT"
8" maple, N.50°W. 5.8' scribed "C¼ S29 BT"
6' Fencepost 1' north.
Note- 1½" Iron pipe set by A.R. Evans in CSF# 41/100 as per
C.E. Roberts Survey, F.B.#7, pg.7. Noted in
CSF#41/293 & CSF# M1-18 as midpoint of North-South
centerline bears S.17°50'43"W. 146.23'.
27" cedar, S.62°E. 32.3', rec. S.65°E. 33.5', Evans
1952
31" cedar, N.52°E. 28', rec. N.53°E. 28.6', Evans 1952.