

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 240340

PRIMARY CORNER DESCRIPTION Center 1/4 Sec. 20

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Adam DeGroot - For: Weyerhaeuser Co. - May 2020 - M178-2  
-----

Set - A 5/8"x30" iron rod, 26" in the ground, with a 2" aluminum cap stamped:

BTS SURVEYING INC  
T24S R3W  
C 1/4 · S20  
2020  
PLS 89398

New BTs- A 11" D.Fir bears N.10°E., 7.6 ft scribed "C 1/4 S20 BT" on dbl blaze.

A 12" D.Fir bears S.76°30'E., 24.6 ft scribed "C 1/4 S20 BT" on dbl blaze.

A 12" D.Fir bears S.14°45'E., 23.9 ft scribed "C 1/4 S20 BT" on dbl blaze.

A 13" D.Fir bears S.76°30'W., 10.4 ft scribed "C 1/4 S20 BT" on dbl blaze.

From this point a 1.5" I.D. x 9.5' Yellow painted iron pipe, loose and leaning, set 18" in the ground bears N.0°24'44"W., 0.66 ft. I remove pipe to set and occupy corner, and reset to mark the corner.