

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCS0 records Vol. 7 Page(s) 3009)

Set cedar post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. marked ¼ sec. cor. mkd. ¼ S on N face from which
A cedar, 12" dia., bears N.61°E., 43 lks., mkd: ¼ S BT.
A dogwood, 10" dia., bears S.9°E., 13 lks., mkd: ¼ S BT.

BLM dependent resurvey by Norman D. Price, Cad. Engineer, under Group 242 surveyed June/Aug. 1950 (DCS0 recs. Vol. 27 Page(s) 11485)

Point for the ¼ sec. cor. of secs. 17 & 20, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:
$$\frac{1}{4} \frac{S \ 17}{S \ 20}$$

1950
from which
A fir, 44" dia., bears N.84°E., 100 lks., mkd: ¼ S17 BT.
A madrona, 6" dia., bears S.78°45'W., 78 lks., mkd: ¼ S20 BT.

Fd. Ok per Weyerhaeuser Co. corner reports Sept. 1958, C.S. File 42/323 & Nov. 1961, C.S. File 51/31-3

Fd. Ok per Peel, M 103-29 Dec. 1986
Fd. Ok per L. Dolan 10/1989 - M109-1
Fd. BC & 1 BT by R. Cook, 8/2009 - M159-67

BLM resurvey by George M. Winter, Cadastral Surveyor under Group No. 2655, surveyed July/Oct. 2012 - (DCS0 records Vol. 58 Page(s) 23018)

The ¼ sec. cor. of secs. 17 and 20, monumented with an iron post, 1" dia., firmly set, projecting 14" above ground, with brass cap (properly) mkd.
from which the remaining bearing tree mkd. by Price in 1950
A fir, 67" dia., bears N.84°E., 66.0 ft., with a healed blaze.
and a bearing tree mkd. by person(s) unknown.
A fir, 19" dia., bears S.41¼°E., 4.2 ft., with a healed double blaze.
Corner is located 77 ft. E. of the intersection of gravel roads, bearing S.55°E, S.75°E, and N.50°W.

continued next page

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Adam DeGroot - For: Weyerhaeuser Co. - May 2020 - M178-2

Found - A 1" iron post, by Price in 1950 per the USBLM
Dependent Resurvey, firmly set and projecting 14"
above ground, with a 2½" brass cap properly
marked per the record.

From which a 1950 BT by Price -

A 65" D.Fir bears N.82°45'E., 65.1 ft w/healed blaze
(N.84°E., 100 lks) BLM 1950 (N.84°E., 66.0) BLM 2012

A BT BY WEYCO -

A 21" D.Fir bears S. 42°45'E., 4.5 ft w/healed blaze
(S. 41°15'E., 4.2') BLM 2012

New BTs- A 8" D.Fir bears S.71°45'W., 37.5 ft scribed "¼ S20
BT" on dbl blaze.

A 8" D.Fir bears N.38°15'W., 38.3 ft scribed "¼ S17
BT" on dbl blaze.

Note - Corner falls ±77 feet east of road intersection