

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 17

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GL0 survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCS0 records Vol. 7 Page(s) 3012)

Set hemlock post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. marked ¼ sec. cor. mkd. ¼ S on W face from which
A hemlock, 8" dia., bears N.22°E., 56 lks., mkd: ¼ S BT.
A cedar, 20" dia., bears S.17°E., 32 lks., mkd: ¼ S BT.

BLM dependent resurvey by Norman D. Price, Cad. Engineer, under Group 242 surveyed June/Aug. 1950 (DCS0 recs. Vol. 27 Page(s) 11488)

Point for the ¼ sec. cor. of secs. 8 & 17, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:
$$\frac{1}{4} \frac{S \ 8}{S \ 17}$$

1950
from which
A fir, 33" dia., bears N.18¼°W., 56 lks., mkd: ¼ S8 BT.
A maple, 18" dia., bears S.11°E., 17 lks., mkd: ¼ S17 BT.

Fd. Ok by WEYCO 9/1957 - C.S. 42/323 & C.S. 51/31-3

Baughman Surveying Service, Eugene Bloom - Feb. 1973 - M47-61 & C.S. File 55/280

Found - Orig. Brass cap
36" D.Fir
20" Maple (dead)
New BTs- 20" Cedar bears N.29°E., 21.1 ft. mkd: N¼ S8 BT.
8" D.Fir bears S.52°30'W., 22.75 ft. mkd: N¼ S17 BT.
Note - The corner is situated on a SW slope, approx. 120 ft. above a medium size creek that courses SE. Medium undergrowth of salal, fern & Oregon grape. Trees of D.Fir & scattered Cedar.

BLM resurvey by George M. Winter, Cadastral Surveyor under Group No. 2655, surveyed July/Oct. 2012 - (DCS0 records Vol. 58 Page(s) 23019-20)

The ¼ sec. cor. of secs. 8 & 17, perpetuated by Bloom, in 1973, monumented with an iron post, 1" dia., firmly set, buried 18" below ground, with brass cap (properly) mkd. from which the remains of a BT mkd. by Price in 1950
A sawed, decayed fir stump, 30" dia., bears N.18¼°W., 37.0 ft., with no marks visible on an open blaze,
continued next page

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and the remains of a bearing tree mkd. by Bloom
A sawed cedar stump, 24" dia., bears N.22 $\frac{3}{4}$ °E., 20.2 ft.,
with no marks visible.
and new bearing trees
A fir, 11" dia., bears N.48 $\frac{3}{4}$ °E., 15.7 ft., mkd. $\frac{1}{4}$ S8 BT.
A fir, 14" dia., bears S.48 $\frac{1}{2}$ °E., 11.6 ft., mkd. $\frac{1}{4}$ S17 BT.
Each new bearing tree has a 2 $\frac{1}{2}$ "x $\frac{1}{4}$ " magnetic nail (Mag Nail)
driven at the base right side-center.
Corner is located 170 ft. N. of a creek, 8 ft. wide, course
S.80°E.