

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 8

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 7 Page(s) 3016)

Set chittim post 3 ft. long, 3" sq., 24" in the ground for 1/4 sec. cor. marked 1/4 sec. cor. mkd. 1/4 S on N face from which
A dogwood, 8" dia., bears N.22°E., 37 lks., mkd: 1/4 S BT.
A maple, 10" dia., bears S.53°E., 44 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Norman D. Price, Cad. Engineer, under Group 242 surveyed June/Aug. 1950 (DCSO recs. Vol. 27 Page(s) 11490-1)

Point for the 1/4 sec. cor. of secs. 5 & 8, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:
1/4 $\frac{S\ 5}{S\ 8}$
1950

from which
A fir, 15" dia., bears N.49 1/4°W., 32 lks., mkd: 1/4 S5 BT.
A cedar, 12" dia., bears S.39°E., 28 lks., mkd: 1/4 S8 BT.

Glen McChesney - For: Weyerhaeuser Co. - Sept. 29, 1977 (Filed 12/1980) - C.S. File 58/8-26

Found - 1950 GLO brass cap
15" now 20" fir, face healed over; also Weyerhaeuser plate & scar of healed over W nail, bears N.50°W., 21.1 ft. center of tree.
12" now 18" R.Cedar, some scribing visible but much of scribing has weathered off; also Weyerhaeuser plate & sq. W nail bears S.42°E., 18.2 ft. center of tree measurement.

Accessories added this date:
36" Fir, N.33°E., 18.1 ft. with "W" nail & plate.
36" Fir, S.88°E., 40.0 ft. with "W" nail & plate.

BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, & Robert Browning, Survey Technician, under Group #11739, surveyed July/Oct. 1994 - (DCSO records Vol. 52 Page(s) 20058-9)

From the 1/4 sec. cor. of secs. 5 & 8, monumented with an iron post, 1" diam., firmly set, projecting 8" above ground, with brass cap (properly) mkd.
from which the remains of bearing trees mkd. by Price

continued next page

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A sawed cedar stump, 24" dia., bears S.39°E., 28 lks., with scribe marks S8 visible on partially healed blaze.
A fir, 25" dia., bears N.49¼°W., 32 lks., with healed blaze.
and the remains of a tree referenced by McChesney in 1977,
A sawed fir stump, 40" dia., bears N.33½°E., 29 lks., with no marks visible.
and a new bearing tree
A hemlock, 7" dia., bears S.74°E., 25½ lks., mkd. ¼ S8 BT.
From this point, the Bureau of L& Management, Geodetic Control Station EC41230, at latitude 43°29'53.088"N., longitude 123° 04' 35.951" W. (NAD 1927), determined by the NAVSTAR Global Positioning System, bears S.9°44'36"E., 31.897 chs., (mean bearing & sea level distance), monumented with an aluminum cap, 3¼" diam., firmly set, projecting 1" above ground, with top mkd. EC41230 GPS 1994.