

PRIMARY CORNER DESCRIPTION Center 1/4 Sec. Cor. 5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Marion Hale - For: Weyerhaeuser Co. - Sept. 1960 - C.S. File 42/323 & 53/111-7

-----  
Set - 7/8" x 38" piece of drill steel for corner by the intersection method.

Ref.- By Hale, Weyerhaeuser method.

Decl. 20°

37" Fir N.42°W., 29.8 ft.

44" Fir S.73°E., 24.3 ft.

BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, & Robert Browning, Survey Technician, under Group #11739, surveyed July/Oct. 1994 - (DCSO records Vol. 52 Page(s) 20059)

-----  
The center ¼ sec. cor. of sec. 5, established by Hale, in 1960, and is accepted as the corner; monumented with a drill steel, 7/8 in. diam., firmly set, projecting 3" above ground, from which the remains of trees referenced by Hale:

A root hole, bears S.73½°E., 36 lks., with down and rotted fir trunk alongside, size indeterminable, with "W" nail driven in at base.

A sawed fir stump, 48" diam., bears N.42¾°W., 45 lks., with "W" nail driven in at base.

At the corner point

Set a stainless steel post, 28" long, 2½" diam., 24" in the ground, with brass cap mkd.

T24S R3W  
C¼ S5  
1994

from which new bearing trees

A hemlock, 17" dia., bears S.38½°E., 8 lks., mkd. X BT.

A hemlock, 15" dia., bears S.57½°W., 12 lks. mkd. C¼ S5 BT

Deposit a white "DEEP-1" magnetic marker at base and drill steel inside the stainless steel post.