

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 32 & 33

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 7 Page(s) 2998)

-----

Set a hemlock post 3½ ft. long, 3x4", 24" in the ground for ¼ sec. cor. marked ¼ sec. cor. mkd. ¼ S on W face from which  
A hemlock, 12" dia., bears S.17°E., 26 lks., mkd: ¼ S BT.  
A cedar, 7" dia., bears S.35°E., 12 lks., mkd: ¼ S BT.

Clifford M. Bryden - May 9, 1957 - C.S. File 42/271

-----

Point for corner located by proportional measurement.  
Set - 1" x 36" iron pipe at corner point.  
5" Hemlock, N.59°W., 32 ft., scribed R.E. 3937 BT.  
22" Fir, S.16°30'E., 9.5 ft., scribed R.E. 3937 BT.