

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Cor. Secs 20, 21, 28, & 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #152, dated June 3, 1871 - (DCSO records Vol. 7 Page(s) 2955)

Set post cor. to secs. 20, 21, 28, & 29 from which
A fir, 30" dia., bears N.35°E., 11 lks.
A cedar, 24" dia., bears S.75°E., 46 lks.
A cedar stub, 24" dia., bears S.50°W., 22 lks.
A yew, 6" dia., bears N.70°W., 16 lks.

Douglas Co. Surveyors Office - Ben B. Irving, Deputy -
Witnesses: Ed Stearns, Chas. Jewell & Roy Abeen - Aug. 11, 1928 - C.S. File 14/65

Location identified from OBTs as follows:
Cedar S.54½°E. 42 lks.
Yew N.85°W., 16 lks. (down)
Cedar snag S.43°W., 22 lks.
Fir N.35°E., 11 lks. (down)
Cedar post scribed as in Orig.
Renewed by setting 5" sq. Yew wood post from which
36" Cedar bears S.54°E., 46 lks.
10" Yew wood bears N.44°W., 26 lks.
8" Fir bears N.52°E., 15 lks.
6" Fir bears S.63½°W., 60 lks.

BLM dependent resurvey by Norman D. Price, Cad. Engineer, under Group 242 surveyed June/Aug. 1950 (DCSO recs. Vol. 27 Page(s) 11473)

Point The cor. of secs. 20, 21, 28 & 29 was remonumented by the county surveyor when the original corner evidence was intact with a yew wood post, 5 ft. long 5 ins. sq., mkd. T24S S21 on NE., R3W, S28 on SE., S29 on SW., and S20 on NW. face; from which the only remaining original bearing tree:
A cedar, 24" dia., bears S.55½°E., 46 lks. surface scar indicating an old blaze. (Rec bearing S.75°E.)
and BTs marked by the county Surveyor
A stumphole, bears N.52°E., 15 lks.
A stumphole, bears S.63½°W., 60 lks.
A yew, 10" dia., bears N.38½°W., 35 lks., with surface scar indicating old blaze. (Rec N.44°W., 26 lks.)
At the corner point
Set an iron post, 3 ft. long, 2" dia., 16" in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.
T24S R3W
S 20 | S 21
S 29 | S 28
continued next page

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Cor. Secs. 20, 21, 28, & 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

from which
A fir, 22" dia., bears S.13°45'W., 55 lks., mkd: T24S R3W S29 BT.
A fir, 50" dia., bears N.81°45'W., 67 lks., mkd: T24S R3W S20 BT.
Reset the yew wood stake inverted & alongside the iron post.

FD. Ok by M. Hale, 7/1959 - C.S. File 51/31-1
Fd. OK by D.Peel, 6/1991 - M113-43

Daniel Baker - Weyerhaeuser Co. - 12/15/94 - M 121 - 58 A&B

Found - 5" Yew Post
GL0 brass cap dated 1950
32" Cedar stump, S.55°E. 28.4' to "W" nail, rec. S.54°E. 46 lks. - 1928 Do. Co.
27" Fir stump, S.15°W. 36.3', to "W" nail, rec. S.13°45'W. 36.3' - 1950 GL0.
50" Fir stump, N.82°W. 46.4', rec. N.81°45'W. 44.2' - 1950 GL0.
11" dead Yew, N.42°W. 16.9', to "W" nail, rec. N.44°W. 26 lks. - 1928 Do. Co.
New BTs - 6" fir, S.62°E. 11.9' to "W" nail, scribed "T24S R3W S28 BT".
12" fir, N.56°E. 15.6' to "W" nail, scribed "T24S R3W S21 BT".
10" fir, S.35°W. 26' to "W" nail, scribed "T24S R3W S29 BT".
7" fir, N.60°W. 5.9' to "W" nail, scribed "T24S R3W S20 BT".

FD. Ok by D. Baker, 6/1996 - M125-33