

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Cor. Secs 16, 17, 20, & 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #152, dated June 3, 1871 - (DCSO records Vol. 7 Page(s) 2955)

Set post cor. to secs. 16, 17, 20, & 21 from which
 An Alder, 10" dia., bears N.70°E., 56 lks.
 An Alder, 12" dia., bears S.10°E., 13 lks.
 An Alder, 40" dia., bears S.50°W., 22 lks.
 An Alder, 6" dia., bears N.20°W., 31 lks.

Fd. & used on GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 7 Page(s) 3009)

BLM dependent resurvey by Norman D. Price, Cad. Engineer, under Group 242 surveyed June/Aug. 1950 (DCSO recs. Vol. 27 Page(s) 11473)

Point for the cor. of secs. 16, 17, 20, & 21 proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap marked:
 T24S R3W
 S 17|S 16
 S 20|S 21
 1950
from which
 A cedar, 8" dia., bears N.18°45'E., 99 lks., mkd: T24S R3W S16 BT.
 A fir, 12" dia., bears S.20¼°E., 139 lks., mkd: T24S R3W S21 BT.
 A fir, 12" dia., bears S.74°W., 179 lks., mkd: T24S R3W S20 BT.
 A fir, 7" dia., bears N.43¼°W., 113 lks., mkd: T24S R3W S17 BT.

FD. Ok by Weyerhaeuser Co., M. Hale, 8/1961 - C.S. 51/31-4
Fd. Ok D. Peel, Dec. 1986, M 103-29
Fd. Ok by Dan Baker, 11/2000 - M136-37
FD. BC & ¾" IP by D. Baker - 10/2009 - M160-23
FD. BC & ¾" IP by D. Baker - 4/2012 - 2012-0007A&B

BLM resurvey by George M. Winter, Cadastral Surveyor under Group No. 2655, surveyed July/Oct. 2012 - (DCSO records Vol. 58 Page(s) 23016)

The cor. of secs. 16, 17, 20, and 21, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap (properly) mkd.
from which the remains of bearing trees mkd. by Price in 1950 continued next page

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Cor Secs 16, 17, 20, & 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A decayed cedar stump, 14" dia., bears N.18¼°E., 65.3 ft., with no marks visible, and a new growth on northwest side, 20" dia., with a copper tag mkd. REG. ENGINEER #2149.

A decayed fir stump, bears S.20¼°E., 91.7 ft., with no marks visible

A sawed, decayed fir stump, 28" dia., bears N.41¼°W., 69.6 ft., with a healed blaze. (Record, N.43¼°W., 74.6 ft.) and new bearing trees

A fir, 13" dia., bears N.49½°E., 23.4 ft., mkd. T24S R3W S16 BT.

A fir, 20" dia., bears S.41°E., 41.8 ft., mkd. T24S R3W S21 BT.

A fir, 10" dia., bears S.79½°W., 39.2 ft., mkd. T24S R3W S20 BT.

A fir, 17" dia., bears N.60½°W., 26.2 ft., mkd. T24S R3W S17 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.
NAD 1983 (2011)
Latitude: 43°28'29.25"N Longitude: 123°04'13.49"W.
From this corner, a point established by person(s) unknown, bears N.31°7'33"E., 4.78 ft., monumented with an iron pipe, 3/4" dia., firmly set, projecting 9" above ground, with no cap. Not utilized in the course of this survey.