

PRIMARY CORNER DESCRIPTION Cor Secs 8, 9, 16 & 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 7 Page(s) 3000)

Set yew post 4 ft. long, 4" sq. 24" in the ground for cor. to secs. 8, 9, 16, & 17 marked T24S S9 on NE., R3W S16 on SE., S17 on SW., & S8 on NW faces with 4 notches on S & E edges from which

- A hemlock, 12" dia., bears N.71°E., 70 lks., mkd: T24S R3W S9 BT.
- A chinquapin, 12" dia., bears S.19°E., 50 lks., mkd: T24S R3W S16 BT.
- A hemlock, 6" dia., bears S.81°W., 13 lks., mkd: T24S R3W S17 BT.
- A hemlock, 8" dia., bears N.48°W., 12 lks., mkd: T24S R3W S8 BT.

BLM dependent resurvey by Norman D. Price, under Group 242 surveyed June/Aug. 1950 (DCSO recs. Vol. 27 Pg 11476)

Point for the cor. of secs. 8, 9, 16, & 17, proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 2" dia., 12" in the ground, to bedrock, & in a mound of stone, 4 ft. base, to top, with brass cap marked:

T24S	R3W
<u>S 8</u>	<u>S 9</u>
S 17	S 16

1950

from which

- A fir, 7" dia., bears N.16°E., 12 lks., mkd: ¼ S9 BT.
- A fir, 7" dia., bears S.89°E., 15 lks., mkd: ¼ S16 BT.
- A fir, 8" dia., bears S.47°45'W., 22 lks., mkd: ¼ S17 BT.
- A fir, 12" dia., bears N.12½°W., 26 lks., mkd: ¼ S8 BT.

The sec cor is located at the head of a small spur slopes NE.

Robert Cook - For: Weyerhaeuser Co. - 12/2010 - M161-57

Found - 1950 GLO brass cap on 1½" pipe up 16" on shoulder of ridge in windfalls; (steep down to north). Set 6' steel post NE 1.0'

- 10" D.Fir windfall (S.89°E 15 lks) healed face & tag
- 24" D.Fir windfall (S.47°45'W 22 lks.) healed face and tag.

New - 11" D.Fir N.68°W 28.3 ft scribed "T24SR3WS8" above "BT"

- 12" D.Fir S36°W 50.0 ft scribed "T24SR3WS17" above "BT"
- 6" Hemlock S83°E 14.0 ft scribed "T24SR3WS16" above "BT"
- 10" Hemlock N28°E 23.4 ft scribed "T24SR3WS9" above "BT".

A 60d nail for control lies S 88°26'02"E 22.20 ft.

Cont.

PRIMARY CORNER DESCRIPTION Cor Secs 8, 9, 16 & 17

Alias	Description

BLM resurvey by George M. Winter, Cadastral Surveyor under Group No. 2655, surveyed July/Oct. 2012 - (DCSO records Vol. 58 Page(s) 23017-8)

The cor. of secs. 8, 9, 16 & 17 perpetuated by Cook, in 2010, monumented with an iron post, 2" dia., firmly set, projecting 15 ins. above ground, with brass cap (properly) mkd.

from which the remains of bearing trees mkd. by Price in 1950

- A roothole bears N.16°E., 7.9 ft., with fallen fir snag, 10" dia., lying downhill, with a healed blaze.
- A roothole bears S.89°E., 9.9 ft., with fallen fir snag, 8" dia., lying downhill, with a healed blaze.
- A roothole bears S.47¼°W., 14.5 ft., with fallen fir snag, 19" dia., lying downhill, with a healed blaze.
- A roothole bears N.12½°W., 17.2 ft., with fallen hemlock snag, 18" dia., lying downhill, with a healed blaze.
(Record, fir.)

and bearing trees mkd. by Cook

- A hemlock, 12" dia., bears N.28¼°E., 23.4 ft., with scribe marks T24S R3W S9 visible on a partially healed blaze.
- A hemlock, 9" dia., bears S.82°E., 14.1 ft., with scribe marks T24S R3W S16 visible on a partially healed blaze.
- A fir, 12" dia., bears S.35¼°W., 50.4 ft., with scribe marks T24S R3W S BT visible on a partially healed double blaze.
- A hemlock, 11" dia., bears N.68½°W., 28.5 ft., with illegible marks visible on a partially healed double blaze.

NAD 1983 (2011)
Latitude: 43°29'21.09"N. Longitude: 123°04'10.92"W.