

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 7 Page(s) 3002)

Set cedar post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. marked ¼ sec. cor. mkd. ¼ S on W face from which
A hemlock, 10" dia., bears S.71°E., 8 lks., mkd: ¼ S BT.
A hemlock, 12" dia., bears N.29°W., 9 lks., mkd: ¼ S BT.

BLM dependent resurvey by Norman D. Price, Cad. Engineer, under Group 242 surveyed June/Aug. 1950 (DCSO recs. Vol. 27 Page(s) 11477-8)

Point for the ¼ sec. cor. of secs. 8 & 9, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft, long, 1" dia., 28" in the ground with brass cap marked:

¼
S 8|S 9
1950

from which

A cedar, 26" dia., bears S.88°E., 60 lks., mkd: ¼ S9 BT.
A hemlock, 18" dia., bears N.16¼°W., 42 lks., mkd: ¼ S8 BT

Robert Cook - For: Weyerhaeuser Co. - 12/2010 - M161-57

Found - 1950 GLO brass cap on ¾" pipe up 6" on SE slope about 100' NE of an old cat road.
50" Cedar S.88°E., 60 lks., healed face, tag & paint
32" Hemlock N.16°30'W., 42 lks., healed face, tag & paint.