

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Reset & remarked 1967 County Surveyors brass cap
T24S R3W ¼ S 5 | S 4 1974 1967 with a steel fence
post alongside, from which
12" Hemlock stump bears N.75¼°E., 50.2 ft.
previously opened blaze & scribing visible. (Rec.
N.75¼°E., 50.2 ft.)
10" Hemlock stump bears S.28¼°W., 49.3 ft. (rec.
S.27°W., 46.3 ft.) scribing "¼ S5 CS BT visible.

BLM dependent resurvey by Bryan S. Seibold, Cadastral
Surveyor, & Robert Browning, Survey Technician, under Group
#11739, surveyed July/Oct. 1994 - (DCS0 records Vol. 52
Page(s) 20060)

The ¼ sec. cor. of secs. 4 & 5, perpetuated by Tracy, in
1967, further perpetuated by Langlitz, in 1974; monumented
with an iron post, 1½" diam., firmly set, projecting 6" above
ground, with brass cap (properly) mkd.
from which the remains of a bearing tree mkd. by Price
A sawed & rotted hemlock stump, size indeterminable, bears
N.72¾°E., 76 lks., with scribe marks ¼ S visible on
rotted blaze. (Record, N.75¼°E.)
and the remains of a bearing tree mkd. by Tracy
A sawed hemlock stump, 10" dia., bears S.26½°W., 74 lks.,
with scribe marks ¼ S5 CS BT visible on open blaze.
and new bearing trees
A fir, 10" dia., bears N.28¾°E., 11 lks., mkd. ¼ S4 BT.
A fir, 12" dia., bears S.70¼°W., 13½ lks., mkd. ¼ S5 BT.

Dan Baker - For: Weyerhaeuser Co. - 12/2005 - M149-70

Found - 1" iron pipe with 2½" DOUGLAS COUNTY BRASS CAP
13" Fir, N.29°E., 7.6' - center measure.
14" Fir, S.70°W., 8.9' - center measure.
Set - 12" Fir, S.49°E., 11.6' to "W" nail scribed "¼S4 BT"
13" Fir, N.46°W., 11.8' to "W" nail scribed "¼S5 BT"
6' fence post set alongside corner.