

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 4; & 33, T23-3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by James P. Currin, Deputy Surveyor, under Contract #438, dated May 2, 1882 - (DCSO records Vol. 5 Page(s) 2213)

-----  
A Hemlock 5" dia., which I mark ¼ S. on N. face for ¼ sec. cor., from which  
    A Cedar 14" dia., bears South, 10 lks. dist. mkd. ¼ S BT  
    A Hemlock 14" dia., bears East, 20 lks. dist. mkd. ¼ S BT  
Corner on E. bank of creek.

Weyerhaeuser Co. - 1958 - C.S. File 53/111-29

-----  
Found - 1882 5" hemlock mkd. ¼ S on N. face, chopped out and found scribing on lower face on N. side of 12" Hemlock.  
    14" Cedar South 6.6 ft., scribing visible on 26" Cedar, (Orig.)  
    14" Hemlock East, 13.2 ft., no trace.  
BTs - 26" Cedar S.13°W., 8.9 ft, "W" nail and plate.  
    10" Hemlock N.2°E., 28.6 ft. "W" nail and plate.

Dan Baker - For: Weyerhaeuser Co. - 12/2005 - M149-70

-----  
Found - 23" cedar snag, S.13°W., 8.9' - to face.  
Set - 1½"x31" iron pipe with brass cap  
    8" Alder, N.38°E., 6.7' - scribed "¼S33 BT"  
    15" Alder, S.84°E., 10.4' - scribed "¼S4 BT"  
    9" Alder, S.2°E., 39.8' - scribed "¼S4 BT"  
    9" Alder, S.65°W., 31.3' - scribed "¼S4 BT"