

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 33 & 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 7 Page(s) 2992)

Set cedar post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. marked ¼ sec. cor. mkd. ¼ S on W face from which
A fir, 30" dia., bears S.64°E., 22 lks., mkd: ¼ S BT.
A cedar, 12" dia., bears N.52°W., 22 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - 9/1966 - C.S. File 54/27

Reported as not found.

Burt Holt - For: Sun Studs Inc. - 12/1981 - M 90-16

Set - 5/8"x30" I.R. 25" in ground, from which:
7" D.Fir bears N.22°E., 11.3 ft., mkd: "¼ S34 BT"
14" D.Fir bears S.26°W., 19.7 ft., mkd: "¼ S33 BT"
Note- This corner lies on spur ridge sloping SW.