

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 22

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars under contract #152, dated June 3, 1871 - (DCSO records Vol. 7 Page(s) 2954)  
-----  
Set ¼ sec. post from which  
    A fir, 6" dia., bears N.25°E., 11 lks.  
    A fir, 5" dia., bears S.60°W., 10 lks.

Fd. & used on GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 7 Page(s) 2996)

WEYCO, Lester E. Calder - April 1964 - C.S. 51/31-5  
-----  
GLO survey rec. 1871 - Post - Gone  
                                    5" Fir, S.60°W., 10 lks. - Gone  
                                    6" Fir, N.25°E., 11 lks. - Gone  
Set - 1" alum. pipe for corner by single proportionate  
      method. Ref by Glen McChesney C.S. 53/111-24)  
      (Weyerhaeuser method with disc. #2149, Decl. 20°)  
      22" Fir N.87°E., 22.0 ft.  
      16" Fir N.52°W., 41.6 ft.

Dan Baker, For: Weyerhaeuser Co. - Dec. 8, 1983 - M90-48  
-----  
Set - 1½x57" iron pipe with brass cap mkd. with standard  
      markings & "PLS 1978"  
      30" Fir, N.88°E., 34.8 ft.  
      22" Fir, N.34°W., 32.8 ft.  
Note- 1" al. pipe set by Weyer. Co. bears N.84°25'51"E., 13.47 ft.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flaese and  
Jeff Lorsung - 12/2/2025 - C.S. File 67/61-50  
-----  
Found - 2½" brass cap at base of boulder. Cap leans S.Ely  
      approx. 0.4 ft.  
      40" tipped out D. Fir. Root hole reasonable to  
      record N.88°E. 34.8 ft.  
      1" alum. Pipe set by Weyerhauser Co. In 1964 bears  
      N.83°E. 13.0 ft. (Rec N.84°25'51"E. 13.47 ft.)  
      re-plumb 1" pipe.  
New - 4" chinquapin N.57°E. 22 ft. scribed X BT on high-  
      low blaze.  
      8" D. Fir S.44°E. 7.8 ft. scribed ¼ S22 BT on double blaze.  
      8" D. Fir S.64°W. 2.3 ft0 scribed ¼ S22 BT on double blaze.  
      10" D. Fir N.8°W. 8.1 ft. scribed ¼21 BT on double blaze.  
Notes - Area burnt 9/2020.  
      Mon is on gentle east slope at toe of fill for  
      logging spur road. Mon is in older reprod approx  
      40 ft. east of short logging spur near it's north  
      end. continued next page

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Compass decl. 14¼°E.  
TRIMBLE GEO XT POSITION  
42.46745549 N.            123.05137978 W.