

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Cor. Secs 15, 16, 21, & 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars under contract #152, dated June 3, 1871 - (DCSO records Vol. 7 Page(s) 2953)

Set post cor. to secs. 15, 16, 21, & 22 from which

- A fir, 5" dia., bears N.70°E., 28 lks.
- A fir, 7" dia., bears S.60°E., 12 lks.
- A fir, 8" dia., bears S.55°W., 6 lks.
- A fir, 5" dia., bears N.40°W., 13 lks.

Douglas Co. Surveyors Office - Arthur Boyer, Deputy - Witnesses: Mr. Thornton, Sr., Ted Shellabarger, Bill Kinsel, Tom Leatherwood, & Claud Willey - May 25, 1939 - C.S. File 16/30

No evidence on ground; set from evidence furnished by Mr. Thornton aged abt. 78 yrs who died in 1942 in spring of yr.; he came to site of corner & showed on the ground where he had seen the corner when he cleaned out brush on the 160 acres cornering on this corner (NW¼22) which he owned the topography and creek to the south check his data & from this the corner was reset; it seems that Mr. Thornton homesteaded the NW¼22. Trees used; also drove auto spring leaf for cor.

- 15" Map. N.0°45'W., 31.4 ft. on slope.
- 8" Cedar N.59½°E., 50.6 ft.
- 24" Fir S.79°E., 89.2 ft.
- 18" Fir S.27½°W., 60. ft.

BLM dependent resurvey by Norman D. Price, Cad. Engineer, under Group 242 surveyed June/Aug. 1950 (DCSO recs. Vol. 27 Page(s) 11474)

The corner of secs. 15, 16, 21, & 22 was remonumented by the county surveyor & duly recorded in the records of Douglas County, OR with an automobile spring leaf, 3 ft. long, 2" wide, 5/16" thick; & has been locally recognized & accepted for many years. I therefore accept this cor. for control of this resurvey.

At the corner point
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T24S	R3W
S 16	S 15
S 21	S 22
1950	

raised a mound of stone, 3 ft. base, 2 ft. high, W of cor.

FD. Ok by Robert Banta, 4/1964 C.S. File 51/31-5

continued next page

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Cor. Secs. 15, 16, 21, & 22

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - Aug. 1967 - C.S. File 54/27-80

Found - 1950 Cad. Brass cap, firmly set & properly marked.
Do not find mound of stone called for.
Find BTs as record in 1939 & 1/2" monel pipe set
alongside.
New BTs- 5" Maple N.79°W., 22.5 ft., mkd: "S16 CS BT"
6" Maple N.8°W., 14.0 ft. mkd: "S16 CS BT"
Note - These are the only trees available. Corner is also
marked by 1½" IP 10 ft. long, 7 ft. above ground.

Dan Baker, For: Weyerhaeuser Co. - Dec. 8, 1983 - M90-48

Found - 1950 US GLO iron pipe with brass cap.
12" Maple, N.10°W., 12.8 ft. (dist. to "W" nail)
8" Maple, N.80½°W., 21.9 ft. (dist. to "W" nail)
New BTs- 10" Fir, S.74°E., 78.5 ft.
9" Fir, S.43°W., 22.8 ft.