

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Cor. Secs. 3, 4, 9, & 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars under contract #152, dated June 3, 1871 - (DCSO records Vol. 7 Page(s) 2952)

Set post cor. to secs. 3, 4, 9, & 10 from which
A maple, 5" dia., bears N.32°E., 25 lks.
A fir, 6" dia., bears S.20°E., 8 lks.
A fir, 5" dia., bears S.62°W., 9 lks.
A maple, 5" dia., bears N.2°W., 26 lks.

Fd. & used on GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 7 Page(s) 3004)

BLM dependent resurvey by Norman D. Price, Cad. Engineer, under Group 242 surveyed June/Aug. 1950 (DCSO recs. Vol. 27 Page(s) 11478-9)

Point for the cor. of secs. 3, 4, 9, & 10 is determined by reference to the remaining orig. BTs, which are as follows:
A vine maple, 6" dia. bears N.32°E., 25 lks., with old blaze decayed.
A hemlock, 12" dia., S.24½°E., 8 lks., mkd: S 10 T24S R3W BT. (Record a fir, 6" dia., bearing S.20°E.)
A hemlock, 14" dia., bears S.70°W., 9 lks., with incomplete scribe marks visible on partially healed old blaze. (Rec. a fir, 5" dia., bearing S.62°W.)

At the corner point

Set an iron post, 3 ft. long, 2" dia., 30" in the ground, with brass cap marked:

T24S R3W
S 4 | S 5
S 9 | S 10
1950

from which

- A hemlock, 20" dia., bears N.45½°E., 69 lks., mkd: T24S R3W S3 BT.
- A yew, 6" dia., bears S.9°45'E., 54 lks., mkd: T24S R3W S10 BT.
- A hemlock, 16" dia., bears S.68°W., 20 lks., mkd: T24S R3W S9 BT.
- A hemlock, 20" dia., bears N.47½°W., 44 lks., mkd: T24S R3W S4 BT.

The sec. cor. is located on top of a mound of earth up-turned by the roots of a fallen tree.

continued next page

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Cor. Secs. 3, 4, 9, & 10

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Dan Baker - For: Weyerhaeuser Co. - 12/2005 - M149-70

Found - 2" iron pipe with USGLO 2½" brass cap 1950
24" Hemlock stump, N.47°W., 29.0'
Set - 11" Fir, N.59°E., 10.6' to "W" nail - scribed
"T24SR3WS3 BT"
17" Fir, S.15°E., 36.5' to "W" nail - scribed
"T24SR3WS10 BT"
10" Fir, S.45°W., 50.8' to "W" nail - scribed
"T24SR3WS9 BT"
13" Fir, N.47°W., 7.9' to "W" nail - scribed
"T24SR3WS4 BT"
6' fence post alongside corner.