

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 4

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by L.H. Wheeler under Contract No. 467 dated April 7, 1883 (DCSO records Vol. 7 Page(s) 3005)

Set a chittim post 4 ft. long, 3x4", 24" in the ground for ¼ sec. cor. marked ¼ sec. cor. mkd. ¼ S on W face from which
A fir, 10" dia., bears S.19°E., 27 lks., mkd: ¼ S BT.
A fir, 8" dia., bears S.33°W., 56 lks., mkd: ¼ S BT.

Weyerhaeuser Co., Warner, Engineer/Surveyor Oct. 1957 assisted by W.Warren Dixon - C.Price & G McChesney survey 1953 - C.S. File 53/111-35

Set - Monel pipe
38" Cedar, N.67°W., 27.5 ft., "W" nail & plate
28" Hemlock N.76°E., 3.2 ft., "W" nail & plate

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - April/May 1968 - C.S. File 54/27

Found monel pipe & Weyerhaeuser stump BTs. No orig. BTs fd.

Dan Baker - For: Weyerhaeuser Co. - 12/2002 & 12/2005 - M149-70

Set - 1½"x30" iron pipe with 2" brass cap mkd: T24S R3W ¼ S4|S3 PLS 1978 2002
13" Hemlock, N.38°E., 16.7' - scribed "¼S3 BT"
15" Fir, S.84°E., 19.5' - scribed "¼S3 BT"
16" Yew, N.89½°W., 14.8' - scribed "¼S4 BT"
18" Yew, N.49½°W., 22.8' - scribed "¼S4 BT"
6' fence post alongside.