

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>GLO survey by W.H. Byars under contract #152, dated June 3, 1871 - (DCSO records Vol. 7 Page(s) 2954)</p> <p>-----</p> <p>Set ¼ sec. post from which A Hemlock, 20" dia., bears N. 8 lks. A Maple, 5" dia., bears S.10°W., 17 lks.</p>
<p>Douglas Co. Surveyors Office - Vernon "Ray" Tracy - - 9/1967 - C.S. File 54/27-94</p> <p>-----</p> <p>Reported as not found. Probably destroyed by old fire, we find intersecting EW-NW blazed lines only.</p>
<p>Dan Baker, For: Weyerhaeuser Co. - Dec. 8, 1983 - M90-48</p> <p>-----</p> <p>Set - 1 5/8"x40" iron pipe with brass cap mkd. with standard markings & "PLS 1978" 17" Fir, S.11°E., 21.3 ft. 18" Fir, N.76°W., 7.3 ft.</p>
<p>Russell Badgley - For: Weyerhaeuser Co. - 1/2021 - M179-5</p> <p>-----</p> <p>Found - A (1983) 2½" brass cap properly marked A rotted D.Fir stump bears S.11°45'E., 22.1 ft burned (S.11°E., 21.3' TO "W" nail) 1983 A 27" D.Fir bears N.70°30'W., 8.2 ft w/healed blaze (N.76°W., 7.3' to "W" nail) 1983</p> <p>New BTs- A 15" D.Fir bears N.29°15'E., 24.2 ft. scribed "¼ S15 BT" on double blaze. A 14" D.Fir bears S.35°15'E., 16.1 ft. scribed "¼ S22 BT" on double blaze. A 7" D.Fir bears S.39°00'W., 19.4 ft. scribed "¼ S22 BT" on double blaze.</p>
<p> </p>