

TOWNSHIP 24 RANGE 03 POINT IDENTIFIER # 460160

PRIMARY CORNER DESCRIPTION N E 1/16 S 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ken Hoffine for Lone Rock Timber Co. - May 1991 - M113-9  
-----  
Set 2" aluminum cap on a 5/8" x 36" iron rod 0.5 feet above ground and marked the following accessories: (cap mkd)  
T24S R3W WM  
S34  
NE•1/16  
1991  
PLS 2291  
11" D. Fir. Bears S.49°W. 18.6 ft. Scribe  
"NE 1/16 S34 BT" and tagged tree.  
20" D. Fir. Bears N.67°E. 6.7 ft. Scribe  
"NE 1/16 S34 BT" and tagged tree.  
Notes - Corner lies on a N.W. 30% slope approx. 10 ft.  
N.20°E. of a large tipped out windfall 50° stump.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 12/4/2025 - C.S. File 67/61-47  
-----  
Found - 2" alum cap on 5/8" iron rod proj. 6".  
Sawn, rotted, burnt 34" x 1½ ft D. Fir stump.  
N.67°E. 6.7 ft. healed blaze. Add 3½" mag nail, top center.  
T24S R3W  
S34  
NE . 1/16  
1991  
PLS 2291  
New - Burnt, pitchy 48"x5 ft. D.fir stump. S.84°W. 16.2 ft. 3½" mag nail right side center.  
Compass decl. 14¼°E.  
O CRS COORDINATE SYSTEM  
COTTAGE GROVE-CANYONVILLE ZONE  
N. 222091.926 E. 243010.042